ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

LL200M 2" LL FM5 Conduit Body

Crouse-Hinds

Catalog Number	LL200M
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Conduit Outlet Body, Malleable Iron, LL Shape, 2"
Weight per unit	5.2 (lbs/each)
Product Category	Bodies & Covers

Features

dimensions	10.5000 IN X 3.3100 IN X 4.1200 IN
Form	Form 5

Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted

Dimensions and Weight

Height	4.12
Hub Size	2 in
Length	10.50
Width	4.12

Descriptions

Description	2" LL FM5 CONDUIT BODY
extra long description	CRS-H LL200M 2 FORM 5 LL COND BODY
Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 conduit outlet body, Malleable iron, LL shape, 2"
Product Type	2 Form 5 LL Cond Body Malleable

Manufacturer Information

Brand	Eaton
GTIN	00782274756189
Manufacturers Part Number	LL200M
UPC	782274756189

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Conduit outlet body

Packaging

Carton	1
Weight Per each	5.15

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 514B, CSA C22.2, CUL