

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

64	8	
E4	ε.	
-		
19.00.4	1	
n	ł.	
Щ.	μ.	

LPCC6 6A 600V TD Class CC Low Peak Fuse

Bussmann Fuses

1d1"	
Catalog Number	LPCC6
Manufacturer	Bussmann Fuses
Description	Low Peak Fuse, Time Delay Fuse Speed, Class CC Fuse, 12 S @ 200% Response Time, 6 A, 600 V Ac;150 V DC, Melamine Tube Material, Dual Element, 0.41 In Diameter, 1.5 IN38.1 MM Overa Length, 0.02 LB
Weight per unit	0.0200 (lbs/each)
Product Category	Current Limiting
eatures	
amperage rating	6 A
class	Class CC
connection	Ferrule End X Ferrule End
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN
element	Dual
media	Yes
imensions and Weight	
Size	13/32 In Diameter X 1-1/2 In Length
escriptions	
Description	6A 600V TD CLASS CC LOW PEAK FUSE
extra long description	BUSS LP-CC-6 LOW PEAK CC TIME DELAY
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior
	performance, Bussmann has the right product for your circuit
	and equipment protection needs. These branch circuit rated,
	600v, 200,000a IR fuses offer exceptional protection in the
	smallest package of any UL class of fuses. Choose from the
	ultimate protection provided by our Low Peak LP-CC fuses, the
	time delay of our FNQ-R's for your control transformer and
	similar control applications or
Special Features	Non-indicating, High in-rush current motor protection
anufacturer Information	
Brand	COOPER BUSSMANN
GTIN	00051712180344
UPC	051712180344
axonomies, Classifications, and	•
Category Description	
Туре	FUSE



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	10
Weight Per each	0.02
Uses, Certifications, and Standards	

standard

CE Marked, RoHS Compliant