

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

LPSRK60SPI 60A Indicating Low Peak Dual Bussmann Fuses

-	
Catalog Number	LPSRK60SPI
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series LPS-RK Fuse, Low-Peak Fuse, 60 A, Dual RK1, With Indicator, Ferrule End X Ferrule End, Time Delay, Current-Limiting, 10 Sec At 500%, 100 Kaic At 300 VDC, 300 Kai At 600 V, Standard, 10, 600 V, 300 VDC
Weight per unit	0.3100 (lbs/each)
Product Category	Small Dimension Fuses
eatures	
amperage rating	60 A
class	
connection	
dimensions	
element	Dural
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
imensions and Weight	
Size	1.06 In Diameter X 5.50 In Length
escriptions	
Description	60A INDICATING LOW PEAK DUAL
extra long description	
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann series LPS-RK fuse, Low-peak fuse, 60 A, Dual, RK1, With Indicator, Ferrule end x ferrule end, Time delay,Current-limiting, 10 sec at 500%, 100 kAIC at 300 Vdc,300 kAIC at 600 V, Standard, 10, 600 V, 300 Vdc
Product Type	Indicating LPS-RK-60SP
Special Features	Electrically Isolated End Cap



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712626309
Manufacturers Part Number	LPS-RK-60SPI
UPC	051712626309
Taxonomies, Classifications, and Ca	tegories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.31
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked