

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



MBG050 1/2" Intersystem Bonding *Bridgeport Fittings*

Catalog Number	MBG050			
Manufacturer	Bridgeport Fittings			
Description	1/2" Mighty-Bond® Intersystem Bonding Bridge and Coupling			
	Combination			
Weight per unit	0.2500 (lbs/each)			
Product Category	Grounding & Bonding Equipment			
Features				
Conductor Size	MCC-050: Copper Conductor Ranges: Solid & stranded #8 to #2 Bare AWG. Aluminum Conductor Range: Stranded #6 to #2 AWG IGB-050: Copper Conductor Ranges and Torques: #14 - #10 Sol/Str Torque 10 in-lbs, #8 Solid Torque 40 in-lbs, #6 - #4 Solid Torque 45 in-lbs			
media	Yes			
Material, Color, and Finish				
Conductor Material	Brass/Stainless Steel/Steel			
Dimensions and Weight				
Size	1/2			
Descriptions				
Description	1/2" INTERSYSTEM BONDING			
extra long description	BPT MBG-050 1/2" INTERSYSTEM BONDIN			
Long Description	1/2" Mighty-Bond® Intersystem Bonding Bridge and Coupling combination			
Product Type	1/2" Intersystem Bonding			
Special Features	Minimum enclosure plate thickness 16 Gauge (0.062 inches)			
Manufacturer Information				
Brand	Bridgeport Fittings			
GTIN	00781747023742			
Manufacturers Part Number	MBG-050			
UPC	781747023742			
Taxonomies, Classifications, and (
Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding			

T

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding
	Fittings & Ground Rods
Type	Intersystem Bonding Bridge

Packaging

onaging	
Carton	1
Package	5
Weight Per each	0.25

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

US	es,	Cer	tifica	itions,	and	Stand	lards
----	-----	-----	--------	---------	-----	-------	-------

Used to bond one continuous length of grounding conductor to an enclosure thru a 1/2" trade size knockout, inside or outside of an enclosure or panel board and provides 3-equipment bonding terminations. Meets the requirement for Intersystem Bonding. Patented
UL