


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Packaging

Carton

Weight

Weight Per each

MCT122SLBKWH250 MC 12/2 SL BK/WH/GN 250'

Soon	
Catalog Number	MCT122SLBKWH250
Manufacturer	Afc Cable
Description	MC Cable, Stranded, 600 V, 250 FT Overall Length, Copper Conductor Material, Thermoplastic Insulation Material, Black, White and Green, 2 Conductors, +90 °C Operating Temperature, 0.147 LB/FT
Weight per unit	0.1470 (lbs/each)
Product Category	Teck
Features	
Conductor Size	12 AWG Conductor And Ground
outside diameter	0.495
Voltage Rating	600
Material, Color, and Finish	
Conductor Material	Solid Copper
Dimensions and Weight	
Length	250 FT Coil
Descriptions	
Description	MC 12/2 SL BK/WH/GN 250'
extra long description	KT 1704B42T00 12-2 MC TUFF 250' COI
Special Features	Cable tray rated, install per NEC; May be surfaced mounted and
	embedded in plaster; Environmental air-handling space
	installation per NEC 300.22; UL Classi?ed 1, 2, and 3 hour through (Fire) penetration product, R-14141; Made in USA of US and/or
	imported materials; ColorSpec ID system
Manufacturer Information	
Brand	AFC CABLE SYSTEMS
GTIN	00077680195340
UPC	077680195340
Taxonomies, Classifications, and	l Categories
Category Description	DV 0 MO
Туре	Traditional Lightweight Type MC Cable With Ground And Neutral

250

147 0.147



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses,	Certifications,	and Standards
-------	-----------------	---------------

es, cei uncations, and standards	
standard	UL 83, 1479, 1569, 1581, 2556 File Number E80042, UL File
	Number R-14141, NEC 230.43, 300.22(C), 392, 396, 330, 501,
	502, 503, 530, 504, 505, 518, 520, 530, 645, Federal Speci?cation
	A-A-59544 (Formerly J-C-30B), Meets OSHA And HUD
	Requirements, ISO 9001 Certified
Temperature Rating	90 Deg C (Dry)