

## Elliott Electric Supply

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

We Deliver...Lower Cost, Quality Products, & Personal Service

		and and		
	1	Artes	-	
	A	-	1	
ø	-			

## PFME30LCYUNV166 Indust-Pfme Led Flood 30000 Lumen 100-277 Vac Crouse-Hinds

Catalog Number	PFME30LCYUNV166		
Manufacturer Description	Crouse-Hinds Eaton Crouse-Hinds Series Pfme Led Floodlight, Cool White, Dimmable Driver, 750W-1000W Hid Equivalent, 50/60 HZ, Polycarbonate Lens, 30000 Lumens, 127 LM/W, Aluminum, Yoke Mount, Standard 120° Angle, >0.90 PF, 120-277 Vac, 127-400		
Weight per unit	VDC, 242W 77.0 (lbs/each)		
Product Category	Lighting		
Features			
dimensions	20.1600 IN X 4.1700 IN X 12.5000 IN		
Descriptions			
Description	INDUST-PFME LED FLOOD 30000 LUMEN 100-277 VAC		
extra long description	CRS-H PFME30LCY-UNV1-66 PFME30LCY-U		
Features	PFME LED floodlights are certified for use wet locations and are UL Listed and CSA certified. These floodlights are suitable for locations requiring continuous and consistent light levels in extreme ambient temperatures and where wet, dusty, hot and/or cold conditions exist.		
Long Description	Eaton Crouse-Hinds series PFME LED floodlight, Cool white, Dimmable driver, 750W-1000W HID equivalent, 50/60 Hz, Polycarbonate lens, 30000 lumens,127 lm/W, Aluminum,Yoke mount,Standard 120° angle, >0.90 PF,120-277 Vac,127-400 Vdc,242W		
Product Type	PFME30LCY-UNV1-66		
Manufacturer Information			
Brand	Eaton		
GTIN	00662276966826		
Manufacturers Part Number	PFME30LCY-UNV1-66		
UPC	662276966826		
Taxonomies, Classifications, and Cate	egories		
Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE LIGHTING		
Туре	FLOODLIGHT		
Packaging			
Carton	1		
Weight Per each	77		



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

Ind Facilities & Factories - Facility: Lighting and Lighting Controls