

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **PPKG1PWH 300W RF Plug-In/Remote White** Lutron

Catalog Number	PPKG1PWH
Manufacturer	Lutron
Description	Lutron Caseta Wireless Single-Pole/3-Way Smart Lighting Lamp Dimmer and Remote Kit, White
Weight per unit	0.4500 (lbs/each)
Product Category	Lighting Dimmers
Features	
media	Yes
Voltage Rating	120
Material, Color, and Finish	
Color	White
Finish	Gloss
<b>Dimensions and Weight</b>	
Size	3.13 x 3.19;79.4 x 55.6
Descriptions	
Description	300W RF PLUG-IN/REMOTE WHITE
extra long description	LUT P-PKG1P-WH Caseta Lamp Dimmer a
Features	Conveniently create just the right light for reading, watching TV or entertaining, with the Lutron Caseta Wireless plug-in lamp dimmer and Pico smart remote control. The plug-in lamp dimme simply plugs into a standard outlet and can be used with up to 2 lamps. Control the lights from anywhere in the room by using the Pico remote control either in your hand, on a tabletop pedestal (sold separately) or by mounting the remote directly to the wall. You can even add a wall switch to control plug-in lamps witho
Long Description	Lutron Caseta Wireless Single-Pole/3-Way Smart Lighting Lamp Dimmer and Remote Kit, White
Product Type	Caséta Lamp Dimmer and Remote Kit
Manufacturer Information	·
manaductar or information	

## Mar

Brand	Lutron	
GTIN	00784276072083	
Manufacturers Part Number	P-PKG1P-WH	
UPC	784276072083	



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	Residential dimmers, motion sensors, controls, & photo cells
Packaging	
Carton	1
Weight Per each	0.45
Uses, Certifications, and Standards	
Application	Lighting Control
environmental conditions	0 to 90% humidity, non-condensing. Indoor use only.
Frequency Rating	50 to 60
Operating Temperature	32 to 104
Uses, Certifications, and Standards Application environmental conditions Frequency Rating	Lighting Control 0 to 90% humidity, non-condensing. Indoor use only. 50 to 60

cULus Listed, NOM Certified