




GE
Lighting

23830 - Q1500T3/CL

GE halogen 1500 watt T3 1-pack

- 240 volts
- GE halogen bulbs deliver crisp, white light. This unsurpassed light quality is ideal for adding depth, drama and interest to any room or space. Use GE halogen specialty bulbs to create a dramatic effect
- Lasts 1.8 years based on 3 hours per day usage
- T3 shape with Recessed Single Contact (R7s) base for use in outdoor carriage and post lights



GENERAL CHARACTERISTICS

| | |
|------------|-------------------------------|
| Lamp Type | Halogen - Single-Ended |
| Bulb | T3 |
| Base | Recessed Single Contact (R7s) |
| Filament | C-8 |
| Rated Life | 2000.0 hrs |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------|----------|
| Initial Lumens | 32000.0 |
| Color Temperature | 3050.0 K |
| Nominal Initial Lumens per Watt | 21 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|------------|
| Wattage | 1500.0 |
| Voltage | 240.0 |
| Burn Position | Horizontal |

DIMENSIONS

| | |
|------------------------------|----------------------|
| Maximum Overall Length (MOL) | 10.0630 in(255.6 mm) |
| Bulb Diameter (DIA) | 0.375 in(9.5 mm) |
| Light Center Length (LCL) | 6.313 in(160.4 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 23830 |
| Description | Q1500T3/CL |
| Standard Package | Case |
| Standard Package GTIN | 10043168238301 |
| Standard Package Quantity | 12 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 12 |
| UPC | 043168238304 |

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Dispose of lamp in a closed container.
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Lamp emits UV radiation which may cause eye/skin injury. RG-3
 - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Turn power off before installing lamp.
- Risk of Fire
 - Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
 - Keep combustible materials away from lamp.
 - Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Do not exceed 110% of rated voltage.
 - Do not touch glass with bare hands.
 - Do not use lamp if outer glass is scratched or broken.
 - Operate lamp only in specified position -- see instructions.
 - Use eye protection when handling lamp.
 - Use in enclosed fixture rated for this product.




GE
Lighting

23830 - Q1500T3/CL

GE halogen 1500 watt T3 1-pack

- 240 volts
- GE halogen bulbs deliver crisp, white light. This unsurpassed light quality is ideal for adding depth, drama and interest to any room or space. Use GE halogen specialty bulbs to create a dramatic effect
- Lasts 1.8 years based on 3 hours per day usage
- T3 shape with Recessed Single Contact (R7s) base for use in outdoor carriage and post lights



GENERAL CHARACTERISTICS

| | |
|------------|-------------------------------|
| Lamp Type | Halogen - Single-Ended |
| Bulb | T3 |
| Base | Recessed Single Contact (R7s) |
| Filament | C-8 |
| Rated Life | 2000.0 hrs |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------------|----------|
| Initial Lumens | 32000.0 |
| Color Temperature | 3050.0 K |
| Nominal Initial Lumens per Watt | 21 |

ELECTRICAL CHARACTERISTICS

| | |
|---------------|------------|
| Wattage | 1500.0 |
| Voltage | 240.0 |
| Burn Position | Horizontal |

DIMENSIONS

| | |
|------------------------------|----------------------|
| Maximum Overall Length (MOL) | 10.0630 in(255.6 mm) |
| Bulb Diameter (DIA) | 0.375 in(9.5 mm) |
| Light Center Length (LCL) | 6.313 in(160.4 mm) |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 23830 |
| Description | Q1500T3/CL |
| Standard Package | Case |
| Standard Package GTIN | 10043168238301 |
| Standard Package Quantity | 12 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 12 |
| UPC | 043168238304 |

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
 - Dispose of lamp in a closed container.
 - Do not use lamp if outer glass is scratched or broken.

Warning

- Lamp emits UV radiation which may cause eye/skin injury. RG-3
 - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Turn power off before installing lamp.
- Risk of Fire
 - Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
 - Keep combustible materials away from lamp.
 - Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Do not exceed 110% of rated voltage.
 - Do not touch glass with bare hands.
 - Do not use lamp if outer glass is scratched or broken.
 - Operate lamp only in specified position -- see instructions.
 - Use eye protection when handling lamp.
 - Use in enclosed fixture rated for this product.