


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





RSRE326H 1"-3/4" Stainless Reducing Bushing

	Robroy/Stainless Steel	Stanliess Reducing Dusining
Catalog Nu	mber	RSRE326H
Manufacturer		Robroy/Stainless Steel
Description		Robroy Stainless Hygienic Reducing Bushings Reduce Conduit Hubs to A Smaller Size. They Are Made Of 316 Stainless Steel and Are Specially Designed For The Hygienic System and Are Provided With A Circular Conduit Entry Gasket Made Of Fda Approved Silicone At The Female Thread and An Extended Design On The Male Threads Allowing For A Sealed Connection.
Weight per	unit	
Product Ca		Payer 9 Cayors
Features		
Material		316
outside dia		1.32
Material, Colo	or, and Finish	
Finish		Brushed
Dimensions a	nd Weight	
Overall Len	•	1.41
Descriptions		
Description		1"-3/4" STAINLESS REDUCING BUSHING
	description	ROB-R RE326H HYG RDC BSHG 1"-3/4" 3
Long Descr	iption	Robroy Stainless Hygienic Reducing Bushings reduce conduit hubs to a smaller size. They are made of 316 stainless steel and are specially designed for the hygienic system and are provided with a circular conduit entry gasket made of FDA approved silicone at the female thread and an extended design on the male threads allowing for a sealed connection.
Product Typ	oe	Hyg RDC BSHG 1"-3/4" 316 W/Cond Ent GSKT
Manufacturer	Information	
Brand		Robroy Stainless
GTIN		00784011919864
Manufactu	rers Part Number	RE326H
UPC		784011919864
Taxonomies,	Classifications, and (Categories
Category D		Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs

T

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,
	Knockout Plugs
Туре	Reducing Bushings

Trade Size

Trade Size 1-1/4



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight	0.2
Weight Per each	0.2
Uses, Certifications, and Standards	
standard	UL 514B, E200413, CSA C22.2 No. 18.1-04, NSF/ANSI/3-A
	14159-1, TYPE 4X,IP69/IP69K