


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





SC30 3/0 Cu Butt Splice Nsi Industries

Catalog Number	SC30
Manufacturer	Nsi Industries
Description	Standardbarrel TINNEDCOPPERSPLICE3/0 Awg Standard Barrel Tinned Coppersplices Is A Type Of Copper Compression Connector That Is Produced From High Conductivity Copper Tubing. They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference Listed For 35KV Maximum When Properly Installed.
Weight per unit	0.0800 (lbs/each)
Product Category	Large Terminals & Connectors
atures	
Material	Copper
Number of Conductors	2
Poles	1
Voltage Rating	600 V

Material, Color, and Finish

Warranty

Color	Orange
Finish	Tin Plated

1 YEAR

Dimensions and Weight

Size	L=1.75 - OD=.620 - ID=.490	

Descriptions

3/0 CU BUTT SPLICE
NSI SC-3/0 CU CMP Splice Short 3 AW
StandardBarrel TinnedCopperSplice3/0 AWG Standard Barrel Tinned CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
StandardBarrel TinnedCopperSplice3/0 AWG Standard Barrel Tinned CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Cu CMP Splice Short 3 Awg
3/0 AWG (STR) - CU Splice



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

м	١.	_		4	c _	_ 1				c _					
ľ	۱,	12	n	111		CI		·Δr	' In	ГЛ	rr	ทว	ıTI	n	n
	v			u	а	L - I	u	C-1	'In	W		110		w	

Brand	NSi
GTIN	00662381037084
Manufacturers Part Number	SC-3/0
UPC	662381037084

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Short Barrel - CU Splice

Packaging

magning .		
Carton	1	
Package	25	
	0.08	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C