

# STEELER Aluminum High-Bay

400W High Pressure Sodium Unit Pack  
400W Metal Halide Unit Pack  
400W Pulse Start Metal Halide Unit Pack


## Applications

Gymnasium • Recreation • Retail  
Transportation • Warehouse

## Specifications

- High efficiency, computer-designed 15" spun aluminum reflector
- Formed steel open-air ballast housing, white finish
- Slide-on die-cast aluminum mounting box with 3/4" tapped conduit opening
- Mogul-base porcelain lamp socket, open rated. 2005 NEC Compliant available
- Lamp included and available in 400W HPS, MH and MHPS
- Field-adjustable ladder brackets with eleven (11) distribution patterns

- Optional 5-Tap, 120/208/240/277/480V, ballast (5T) reduces inventory and ordering errors
- Optional Quartz Restrike (Q) for hot strike after momentary power interruption, 250W (max) lamp included
- Minimum starting temperature is -40°C (-40°F) for HPS and 30°C (-20°F) for MH and MHPS
- U.L. listed for damp location. CSA certified
- 65°C (149°F) ambient operation
- Approx. net weight: 30 lbs. (13 kgs.)




## Photometry

Mounting Height	Footcandle Value for Isofootcandle lines				
	A	B	C	D	E
25'	5.00	2.00	1.00	.50	.20
30'	3.47	1.39	.69	.35	.14
35'	1.63	.65	.33	.16	.07

Example of 400W MH at 25ft. mounting height, 36,000 lumen lamp

Watts	Multiplier		
	HPS	MH	MP
400	1.29	1.00	1.22



## Accessories



**Cord (C3)**  
3' 16/3 white cord  
(order hook separately)



**Cord & Plug (PC3-480V)**  
3' Cord with NEMA 480V L8-20P Plug



**Wire Guard (WG15)**  
Heavy-gauge 15" wire guard provides additional lamp protection



**Cord & Plug (PC3-120V)**  
3' Cord with NEMA 120V L5-15P Plug



**Hook (FH-1)**  
Die-cast aluminum hook with 3/4" threads



**Safety Hook (SHK)**  
Die-cast aluminum hook with safety screw and 3/4" threads



**Cord & Plug (PC3-208V)**  
3' Cord with NEMA 208V L6-15P Plug



**Loop (FL-1)**  
Malleable iron plated fixture loop with 3/4" threads



**Thru-Way Mounting Box (TWMBS)**  
Surface mounted thru-way mounting box objects



**Cord & Plug (PC3-240V)**  
3' Cord with NEMA 240V L6-15P Plug



**Safety Glass (SGB15)**  
Safety glass bottom for 15" aluminum reflector, not compatible with WG15. 2005 NEC Compliant



**Wire Guard w/Safety Glass (WG15/GLC)**  
Heavy-gauge 15" wire guard and safety glass lens provides additional lamp protection



**Cord & Plug (PC3-277V)**  
3' Cord with NEMA 277V L7-15P Plug

# STEELER Aluminum High-Bay

400W High Pressure Sodium Unit Pack  
400W Metal Halide Unit Pack  
400W Pulse Start Metal Halide Unit Pack


## Applications

Gymnasium • Recreation • Retail  
Transportation • Warehouse

## Specifications

- High efficiency, computer-designed 15" spun aluminum reflector
- Formed steel open-air ballast housing, white finish
- Slide-on die-cast aluminum mounting box with 3/4" tapped conduit opening
- Mogul-base porcelain lamp socket, open rated. 2005 NEC Compliant available
- Lamp included and available in 400W HPS, MH and MHPS
- Field-adjustable ladder brackets with eleven (11) distribution patterns

- Optional 5-Tap, 120/208/240/277/480V, ballast (5T) reduces inventory and ordering errors
- Optional Quartz Restrike (Q) for hot strike after momentary power interruption, 250W (max) lamp included
- Minimum starting temperature is -40°C (-40°F) for HPS and 30°C (-20°F) for MH and MHPS
- U.L. listed for damp location. CSA certified
- 65°C (149°F) ambient operation
- Approx. net weight: 30 lbs. (13 kgs.)




## Photometry

Mounting Height	Footcandle Value for Isofootcandle lines				
	A	B	C	D	E
25'	5.00	2.00	1.00	.50	.20
30'	3.47	1.39	.69	.35	.14
35'	1.63	.65	.33	.16	.07

Example of 400W MH at 25ft. mounting height, 36,000 lumen lamp

Watts	Multiplier		
	HPS	MH	MP
400	1.29	1.00	1.22



## Accessories



**Cord (C3)**  
3' 16/3 white cord  
(order hook separately)



**Cord & Plug (PC3-480V)**  
3' Cord with NEMA 480V L8-20P Plug



**Wire Guard (WG15)**  
Heavy-gauge 15" wire guard provides additional lamp protection



**Cord & Plug (PC3-120V)**  
3' Cord with NEMA 120V L5-15P Plug



**Hook (FH-1)**  
Die-cast aluminum hook with 3/4" threads



**Safety Hook (SHK)**  
Die-cast aluminum hook with safety screw and 3/4" threads



**Cord & Plug (PC3-208V)**  
3' Cord with NEMA 208V L6-15P Plug



**Loop (FL-1)**  
Malleable iron plated fixture loop with 3/4" threads



**Thru-Way Mounting Box (TWMBS)**  
Surface mounted thru-way mounting box objects



**Cord & Plug (PC3-240V)**  
3' Cord with NEMA 240V L6-15P Plug



**Safety Glass (SGB15)**  
Safety glass bottom for 15" aluminum reflector, not compatible with WG15. 2005 NEC Compliant



**Wire Guard w/Safety Glass (WG15/GLC)**  
Heavy-gauge 15" wire guard and safety glass lens provides additional lamp protection



**Cord & Plug (PC3-277V)**  
3' Cord with NEMA 277V L7-15P Plug