

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TY526M 11" "Ty-Rap" Cable Tie Abb Installation Products, Inc

Catalog Number	TY526M
Manufacturer	Abb Installation Products, Inc
Description	Cable Tie, Natural Polyamide (Nylon 6.6) For Temperatures Up to 85 Degrees Celsius (185 F) For Indoor Applications, Length Of 281.94MM (11.10 Inches), Width Of 3.6MM (0.14 Inches), Tensile Strength Rating Of 134 Newtons (30 Pounds), Bulk
Weight per unit	0.0025 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
Bundle Diameter	0.08 to 2.99 in , 2 to 76 mm
Material	Nylon/Polyamide 6.6
Tensile Strength	30 pounds , 134 newtons
Material, Color, and Finish	
Color	lvory
Dimensions and Weight	
Length	10.9 in , 277 mm
Thickness	0.04 in , 1.0 mm
Width	0.14 in , 3.6 mm
Descriptions	
Description	11" "TY-RAP" CABLE TIE
extra long description	ABB TY526M CBL TIE 30LB 11.10 PO NA
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, Length of 281.94mm (11.10 Inches), Width of 3.6mm (0.14 Inches), Tensile Strength Rating of 134 Newtons (30 pounds), bulk
Product Type	CBL Tie 30LB 11.10 Po Nat Nylon
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time
Manufacturer Information	
Brand	Ty-Rap
GTIN	00786210825496
Manufacturers Part Number	TY526M
UPC	786210825496



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	HIGH PERFORMANCE
Packaging	
Carton	100
Package	500
Weight Per each	0.0025
Uses, Certifications, and Standa	ards

UL E49405