

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UNF305 1" Female Union

Crouse-Hinds

Description

UNF305	
Crouse-Hinds	
	de Size, Unf Model, Straight, Electro Galvanized e Treatment, Female Connection, 2 In Length, ter, 0.77 LB
0.7700 (lbs/ea Rigid Conduit	•
Union, 1 In Tra With Chromat 1-7/8 In Diam	e Treatment, Female Connection, 2 In Length, ter, 0.77 LB ch)

Features

connection	Threaded
dimensions	2.0900 IN X 2.1900 IN X 2.1900 IN

Descriptions

extra long description	CRS-H UNF305 1 NPT FEMALE UNF UNION
Features	Crouse-Hinds series explosionproof unions are installed in
	rigid/IMC conduit systems to connect conduit to conduit, a
	conduit fitting, junction box or device enclosure. Expansion
	unions are also available, which allow for expansion and
	contraction of conduit and compensate for conduit cut too short.
	Available in a variety of materials, including stainless steel, to
	suit customer preferences. Explosionproof elbows allow for a 90°
	change in direction to the conduit run, or when terminating at a

1" FEMALE UNION

Manufacturer Information

Brand	Eaton
GTIN	00782274644103
UPC	782274644103

box or fit

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Union

Packaging

99		
Carton	1	
Package	5	
Weight Per each	0.77	

Uses, Certifications, and Standards

Enclosure	Class I Div 1 2 Group B C D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2