Eaton V48M28T4916

Catalog Number: V48M28T4916

Eaton General purpose ventilated transformer, Fungus proof, AL windings, DOE 2016, NEMA 2, FR943, 220°C, 150 kVA, Fl/wall mt uprt, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 150 kVA, WS60, 280B

General specifications



Catalog Number

Eaton General purpose ventilated

V48M28T4916

transformer

UPC

786680147272

Product Length/Depth

Product Height

31.5 in

51 in

Product Width

Product Weight

34.5 in

1220 lb

Warranty

Compliances

Eaton Selling Policy 25-000, one (1) year DOE2016 Efficient

from the date of installation of the

Certifications

Product or eighteen (18) months from the

UL Listed

Catalog Notes

whichever occurs first.

10 CFR Part 431 (2016) Efficient

date of shipment of the Product,



Photo is representative



defaultTaxonomyAttributeLabel

Special features

Fungus-resistent varnished core and coil

Type

Energy-efficient ventilated dry-type transformer

Coil material

Aluminum

Efficiency

10 CFR Part 431-2016 (DOE 2016)

Frequency rating

60 Hz

Kva Rating

150 kVA

Mounting

Floor or wall, upright only

Phase

Three-phase

Primary voltage

480 V delta

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

150 °C rise

Voltage rating

480 Vac-208Y/120 Vac

Enclosure

NEMA 2

Frame

FR943

Insulation

220 °C

Tap size

2 at +2.5%, 4 at -2.5%

Resources

Brochures

Eaton's high-efficiency dry-type transformers

Eaton's low-voltage dry-type distribution transformers

Specifications and datasheets

Eaton Specification Sheet - V48M28T4916

Volt ampere rating

150 kVA

Weathershield

WS60

Wiring connection

280B



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia