

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**UPC** 

## **X68 2" X FM8 Conduit Body** *Crouse-Hinds*

Catalog Number	X68
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Conduit Outlet Body, Feraloy Iron Alloy, X Shape, 2"
Weight per unit	9.9 (lbs/each)
Product Category	Bodies & Covers
Features	
connection	Threaded / Set Screw
dimensions	
Form	Γο. w Γ
Material, Color, and Finish	
Finish	Hot Dip Galvanized
Dimensions and Weight	
Height	1.97
Hub Size	
Length	
Width	2.02
Descriptions	
Description	2" X FM8 CONDUIT BODY
extra long description	CRS-H X68 2 NPT X FORM 8 CNDT OUTLE
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds
	series. The line has grown to six families manufactured in a
	variety of materials, and Form 8 bodies are offered in seven
	different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for
	heavier conductors. Many shapes and sizes are available for rigid
	threaded conduit. Two cover screws on all body sizes provide
	tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 conduit outlet body,
	Feraloy iron alloy, X shape, 2"
Product Type	2 NPT X Form 8 CNDT Outlet Body
Special Features	Weight 172 Lb per 100
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274746906

782274746906



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	1
Weight Per each	9.9499
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Condulet

UL 514B, CSA C22.2, CUL