

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



XHHW300BKPCS AI XHHW 300 STR Black PCS King Wire Inc.

King vvire inc.		
Catalog Number	XHHW300BKPCS	
Manufacturer	King Wire Inc.	
Description	Aluminum Building Wire, Abrasion, Moisture, Heat and Sunlight Resistant Insulation; Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Black, Aluminum Conductor Material, 300 MCM Conductor Size, 255 A Current Rating, Polyethylene Insulation Material, 65 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 0.705 In Outsic Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec; Federal Specific	
Weight per unit	0.3440 (lbs/ft)	
Product Category	XHHW-STR (Stranded)	
Descriptions Description	AL XHHW 300 STR BLACK PCS	
Manufacturer Information Brand	Aluminum	
Taxonomies, Classifications, and Ca	ategories	

Taxo

Category Description ALUM BUILDING WIRE

Packaging

Carton	1	
Weight Per foot	0.344	