

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



XJG34HDG 1X4" HDG Expn CPLG Crouse-Hinds

Catalog Number	XJG34HDG
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series XJG Expansion Coupling, Rigid/Imc, Steel, Hot Dip Galvanized Finish, 4" Maximum Conduit Movement, 1" Trade Size
Weight per unit	2.8 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
eatures	
dimensions	7.3800 IN X 2.4300 IN X 2.4300 IN
laterial, Color, and Finish	
Finish	Hot Dip Galvanized
escriptions	
Description	1X4" HDG EXPN CPLG
extra long description	CRS-H XJG34 HDG 1 CND EXP JNT INT G
Features	"XJG conduit expansion couplings for EMT and rigid/IMC are use with EMT, rigid metal conduit and IMC to couple together two sections of conduit subject to longitudinal movement. They are installed indoors or outdoors in long conduit runs to permit linear movement caused by thermal expansion and contraction to prevent damage to conduit supports and electrical systems in building or bridges. XJGs for rigid/IMC and EMT are also available with a hot dip galvanized finish (standard for trade sizes 1-1/4"" and
Long Description	Eaton Crouse-Hinds series XJG expansion coupling, Rigid/IMC, Steel, Hot dip galvanized finish, 4" maximum conduit movement 1" trade size
Product Type	1 CND Exp JNT Int GRD Max CND MVT 4 HDG
lanufacturer Information	
Brand	Eaton
GTIN	00662276290174
Manufacturers Part Number	XJG34 HDG
UPC	662276290174

Tax

Category Description	COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS
Туре	Expansion coupling

Packaging

Carton	1	
Weight Per each	2.75	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
Enclosure	NEMA FB1
standard	UL 514B, CSA C22.2