

Eaton XTCEXFAC04

Catalog Number: XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC04
UPC	Product Length/Depth
782116354559	1.5 in
Product Height	Product Width
1.3 in	1.5 in
Product Weight	Compliances
0.12 lb	CCC Marked
	CE Marked
	ATEX Compliant
Certifications	Catalog Notes
IEC 60947	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.
EN 60947	
UL Listed	
CSA Certified	

defaultTaxonomyAttributeLabel

Number Of Poles

Four-pole

Type

Contactor Accessory - Auxiliary Contact

Used with

XTRE control relays

Terminals

Screw

Contact configuration

4 NC

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Special features

Used with XTRE control relays

Conventional thermal current

16A

Quantity

5

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC04](#)

[Global Data Sheet - XTCEXFAC04](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)

Eaton XTCEXFAC04

Catalog Number: XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC04
UPC	Product Length/Depth
782116354559	1.5 in
Product Height	Product Width
1.3 in	1.5 in
Product Weight	Compliances
0.12 lb	CCC Marked
	CE Marked
	ATEX Compliant
Certifications	Catalog Notes
IEC 60947	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.
EN 60947	
UL Listed	
CSA Certified	

defaultTaxonomyAttributeLabel

Number Of Poles

Four-pole

Type

Contactor Accessory - Auxiliary Contact

Used with

XTRE control relays

Terminals

Screw

Contact configuration

4 NC

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Special features

Used with XTRE control relays

Conventional thermal current

16A

Quantity

5

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC04](#)

[Global Data Sheet - XTCEXFAC04](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

