



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## OTS3 600V 3A 5X13/16 K5 Fuse

*Mersen Fuses*

Catalog Number	OTS3
Manufacturer	Mersen Fuses
Description	Fuse Ots - Class K5 - Fast-Acting 600VAC 300VDC 3A Ferrule Amp-Trap®
Weight per unit	0.1100 (lbs/each)
Product Category	Renewable & Non-Renewable

### Features

AC Voltage Rating	600
amperage rating	3
class	K-5
connection	Ferrule
DC Voltage Rating	300
interrupt rating	50
Voltage Rating	600

### Material, Color, and Finish

Body Material	Paper
---------------	-------

### Dimensions and Weight

Size	5 x 0.81
------	----------

### Descriptions

Description	600V 3A 5X13/16 K5 FUSE
extra long description	Mersen OTS3 Fuse OTS - Class K5 - F
Features	One-Time OTS general purpose fuses provide low cost protection for feeder and branch-circuits serving lighting, heating, and other non-motor loads. OTS fuses will safely interrupt available short circuit currents up to 50,000 amperes in all ratings. OTS fuses are not rejection fuses and care should be taken to ensure that replacement fuses do not have lower interrupting ratings than original fuses.
Long Description	Fuse OTS - Class K5 - Fast-Acting 600VAC 300VDC 3A Ferrule Amp-Trap®
Product Type	Fuse Ots - Class K5 - Fast-Acting 600VAC 300VDC 3A Ferrule
Short Description	600V 3A 5x13/16 K5 FUSE
Special Features	Easy to read imprint label for quick recognition and replacement Low cost for high protection value



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	Mersen
GTIN	00782001700621
Manufacturers Part Number	OTS3
sub brand	Amp-Trap <sup>®</sup>
UPC	782001700621

## Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	CLASS K5

## Packaging

Carton	1
Package	10
Weight Per each	0.11

## Uses, Certifications, and Standards

Application	Feeders Branch circuits Resistive heating Residential and small commercial installations
Mounting	Clip
standard	UL Listed to Standard 248-9 File E2137 CSA Certified to Standard C22.2 No. 248.9 (The Canadian Electrical Code requires these fuses in ratings 15 through 60A to be of the low melting point design use OTN 15-60.) Self-certified for DC per UL248