

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



1037NI 2-1/2" Non-Ins Threaded Bushing *Crouse-Hinds*

| Catalog Number | 1037NI |
|------------------|--|
| Manufacturer | Crouse-Hinds |
| Description | Eaton Crouse-Hinds Series Throat Bushing, Rigid/Imc, |
| | Non-Insulated, Malleable Iron, Threaded, 2-1/2" |
| Weight per unit | 0.4400 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |
| | |

Features

| connection | Threaded |
|------------|----------------|
| Material | Malleable Iron |

Dimensions and Weight

| Size | 2-1/2 in |
|--|----------|
| 17. 1 7. 17. 1 7. 17. 17. 17. 17. 17. 17. 17. 17. 17. 1 | |

Descriptions

| Description | 2-1/2" NON-INS THREADED BUSHING |
|------------------------|---|
| extra long description | CRS-H 1037NI 2-1/2" NON-INSULATED T |
| Features | Insulating and throat bushings from Eaton's Crouse-Hinds Division are used on threaded rigid or IMC conduit to prevent wires from being damaged by sharp edges. They are available in threaded and threadless versions. |
| Long Description | Eaton Crouse-Hinds series throat bushing, Rigid/IMC, Non-insulated, Malleable iron, Threaded, 2-1/2" |
| Product Type | 2-1/2" Non-Insulated Threaded Bushing |
| Special Features | Weight 44 Lb per 100 |

Manufacturer Information

| Brand | EATON CROUSE-HINDS SERIES |
|---------------------------|---------------------------|
| GTIN | 00662277003476 |
| Manufacturers Part Number | 1037NI |
| UPC | 662277003476 |

Taxonomies, Classifications, and Categories

| Category Description | Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, |
|----------------------|--|
| | Knockout Plugs |
| Туре | Throat bushing |

Packaging

| ckayırıy | | |
|-----------------|------|--|
| Carton | 1 | |
| Package | 10 | |
| Weight Per each | 0.44 | |
| | | |

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | Commercial / Institutional Buildings / Structures - Commercial / |
|--------------------|--|
| | Institutional Buildings / Structures - Other |
| standard | UL, cUL |
| Temperature Rating | 105 DEG C |