



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 South Street  
75964-7263, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 115 True RMS Multimeter

*Fluke Electronics*

Catalog Number	115
Manufacturer	Fluke Electronics
Description	True RMS Digital Multimeter, LCD Display, 9 V Alkaline Battery, 400 H Battery Life, 3.31 In Length, 1.82 In Width, 6.57 In Height, 5 HZ to 9999 HZ, Cat Iii Safety Category Level
Weight per unit	1.7 (lbs/each)
Product Category	Test Equipment - Multimeters

### Features

Accuracy	0.5 % + 2 V
battery	9 Volt Alkaline, NEDA 1604A / IEC 6LR61
dimensions	6.58 x 3.35 x 1.81 IN
diode test	Yes Yes/No
display	Digital: 6,000 counts, updates 4/sec; Bar Graph: 33 segments, updates 32/sec
Voltage Rating	600 VAC

### Descriptions

Description	TRUE RMS MULTIMETER
-------------	---------------------

### Manufacturer Information

Brand	FLUKE
GTIN	00095969324182
Model	FLUKE 115 V
UPC	095969324182

### Taxonomies, Classifications, and Categories

Category Description	TEST EQUIPMENT, TESTERS AND METERS
Type	DIGITAL MULTIMETER

### Packaging

Carton	1
Weight Per each	1.7


### Uses, Certifications, and Standards

Application	Compact true-rms meter for field service technicians
Enclosure	Hard plastic
standard	CAT III 600 V
Temperature Rating	-10 to 50 C

# Fluke 114, 115, 116 and 117 Digital Multimeters Extended specifications

## Technical Data

### General specifications (all models)

Accuracy is specified for 1 year after calibration, at operating temperatures of 18 °C to 28 °C, with relative humidity of 0 % to 90 %.	
<b>Maximum voltage between any terminal and earth ground</b>	600 V
<b>Surge protection</b>	6 kV peak per IEC 61010-1 600 V CAT III, Pollution Degree 2
<b>Ω Fuse for A input</b>	11 A, 1000 V FAST 17 kA Fuse (Fluke PN 803293)
<b>Display</b>	Digital: 6,000 counts, updates 4/sec; Bar Graph: 33 segments, updates 32/sec
<b>Temperature</b>	Operating: -10 °C to +50 °C; Storage: -40 °C to +60 °C
<b>Humidity</b>	0 % to 90 % to 35 °C; 75 % to 40 °C; 45 % to 50 °C
<b>Temperature coefficient</b>	0.1 x (specified accuracy/°C) (< 18 °C or > 28 °C)
<b>Operating altitude</b>	2,000 meters
<b>Battery</b>	9 Volt Alkaline, NEDA 1604A/IEC 6LR61
<b>Battery life</b>	Alkaline: 400 hours typical, without backlight
<b>Safety compliances</b>	ANSI/ISA 82.02.01 (61010-1) 2004, CAN/CSA C22.2 No 61010-1-04, UL 6101B (2003) and IEC/EN 61010-1 2 <sup>nd</sup> Edition for measurement Category III, 600 V, Pollution Degree 2, EMC EN61326-1
<b>Certifications</b>	UL, CSA, TUV, N10140  , VDE
<b>IP rating (dust and water protection)</b>	IP42

### Accuracy specifications (all models)

Function	Range	Resolution	Accuracy ± ([% of Reading] + [Counts])		Model
DC millivolts	600.0 mV	0.1 mV	0.5 % + 2		114, 115, 116, 117
DC volts	6.000 V 60.00 V 600.0 V	0.001 V 0.01 V 0.1 V	0.5 % + 2		114, 115, 116, 117
			<b>DC, 45 Hz to 500 Hz</b>	<b>500 Hz to 1 kHz</b>	
Auto-V LoZ <sup>1</sup> true-rms	600.0 V	0.1 V	2.0 % + 3	4.0 % + 3	114, 116, 117
			<b>45 Hz to 500 Hz</b>	<b>500 Hz to 1 kHz</b>	
AC millivolts <sup>1</sup> true-rms	600.0 mV	0.1 mV	1.0 % + 3	2.0 % + 3	114, 115, 116, 117
AC volts <sup>1</sup> true-rms	6.000 V 60.00 V 600.0 V	0.001 V 0.01 V 0.1 V	1.0 % + 3	2.0 % + 3	114, 115, 116, 117
Continuity	600 Ω	1 Ω	Beeper on < 20 Ω, off > 250 Ω; detects opens or shorts of 500 μs or longer		114, 115, 116, 117
Ohms	600.0 Ω 6.000 kΩ 60.00 kΩ 600.0 kΩ 6.000 MΩ 40.00 MΩ	0.1 Ω 0.001 kΩ 0.01 kΩ 0.1 kΩ 0.001 MΩ 0.01 MΩ	0.9 % + 2 0.9 % + 1 0.9 % + 1 0.9 % + 1 0.9 % + 1 1.5 % + 2		114, 115, 116, 117
Diode test	2.000 V	0.001 V	0.9 % + 2		115, 116, 117
Capacitance	1000 nF 10.00 μF 100.0 μF 9999 μF	1 nF 0.01 μF 0.1 μF 1 μF	1.9 % + 2 1.9 % + 2 1.9 % + 2 100 μF to 1000 μF: 1.9 % + 2 > 1000 μF: 5 % + 20		115, 116, 117
LoZ capacitance (power-up option)	1 nF to 500 μF		10 % + 2 typical		115, 116, 117

<sup>1</sup> All ac ranges except Auto-V LoZ are specified from 1 % to 100 % of range. Auto-V LoZ is specified from 0.0 V. Because inputs below 1 % of range are not specified, it is normal for this and other true-rms meters to display non-zero readings when the test leads are disconnected from a circuit or are shorted together. For volts, crest factor of ≤ 3 at 4000 counts, decreasing linearly to 1.5 at full scale. For amps, crest factor of ≤ 3. AC volts is ac-coupled. Auto-V LoZ, ac mV, and ac amps are dc-coupled.

**Accuracy specifications (all models) cont.**

Function	Range	Resolution	Accuracy ± ([% of Reading] + [Counts])	Model
Temperature (K-Type thermocouple)	-40 °C to 400 °C -40 °F to 752 °F	0.1 °C 0.2 °F	1 % + 10 <sup>2</sup> 1 % + 18 <sup>2</sup>	116
AC amps true-rms <sup>1</sup> (45 Hz to 500 Hz)	6.000 A 10.00 A 20 A overload for 30 seconds maximum	0.001 A 0.01 A	1.5 % + 3	115, 117
AC µAmps true-rms <sup>1</sup> (45 Hz to 1 kHz)	600.0 µA	0.1 µA	1.5 % + 3 (2.5 % + 3 > 500 Hz)	116
DC amps	6.000 A 10.00 A 20 A overload for 30 seconds maximum	0.001 A 0.01 A	1.0 % + 3	115, 117
DC µAmps true-rms	600.0 µA	0.1 µA	1.0 % + 2	116
Hz (V or A input) <sup>2</sup>	99.99 Hz 999.9 Hz 9.999 kHz 50.00 kHz	0.01 Hz 0.1 Hz 0.001 kHz 0.01 kHz	0.1 % + 2	115, 117
Hz (V input) <sup>3</sup>	99.99 Hz 999.9 Hz 9.999 kHz 50.00 kHz	0.01 Hz 0.1 Hz 0.001 kHz 0.01 kHz	0.1 % + 2	116

<sup>1</sup> All ac ranges except Auto-V LoZ are specified from 1 % to 100 % of range. Auto-V LoZ is specified from 0.0 V. Because inputs below 1 % of range are not specified, it is normal for this and other true-rms meters to display non-zero readings when the test leads are disconnected from a circuit or are shorted together. For volts, crest factor of ≤ 3 at 4000 counts, decreasing linearly to 1.5 at full scale. For amps, crest factor of ≤ 3. AC volts is ac-coupled. Auto-V LoZ, ac mV, and ac amps are dc-coupled.

<sup>2</sup> AC Volts Hz is ac-coupled and specified from 5 Hz to 50 kHz. AC Amps Hz is dc-coupled and specified from 45 Hz to 5 kHz. Amps input burden voltage (typical): 6 A input 2 mV/A, 10 A input 37 mV/A.

<sup>3</sup> Frequency is ac-coupled, 45 Hz to 50 kHz.

**Frequency counter sensitivity (models 115, 116, 117)**

Input range		Typical sensitivity (rms sine wave)			
		5 Hz to 45 Hz	45 Hz to 5 kHz	5 kHz to 10 kHz	10 kHz to 50 kHz
Volts AC	6 V	0.2 V	0.2 V to 0.3 V	0.3 V to 0.4 V	0.4 V to 1.0 V
	60 V 600 V	2 V 20 V	2 V to 3 V 20 V to 30 V	3 V to 4 V 30 V to 40 V	4 V to 10 V 40 V to 100 V
AC Amps (115, 117 only)	6 A	N/A	0.4 A	N/A	N/A
	10 A	N/A	0.5 A	N/A	N/A

**Input characteristics (all models)**

Function	Input impedance (nominal)	Common mode rejection ratio(1 kΩ unbalanced)		Normal mode rejection
Volts AC	> 5 MΩ < 100 pF	> 60 dB at dc, 50 or 60 Hz		
Volts DC	> 10 MΩ < 100 pF	> 100 dB at dc, 50 or 60 Hz		> 60 dB at 50 or 60 Hz
Auto-V LoZ	~3 kΩ < 500 pF	> 60 dB at dc, 50 or 60 Hz		
	Open circuit test voltage	Full scale voltage		Short circuit current
Ohms	< 2.7 V dc	To 6.0 MΩ	40 MΩ	< 350 µA
		< 0.7 V dc	< 0.9 V dc	
Diode Test	< 2.7 V dc	2.000 V dc		< 1.2 mA

**Fluke. Keeping your world up and running.™**

**Fluke Corporation**  
PO Box 9090, Everett, WA USA 98206

**Fluke Europe B.V.**  
PO Box 1186, 5602 BD  
Eindhoven, The Netherlands

**For more information call:**  
In the U.S.A. (800) 443-5853 or  
Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0) 40 2675 200 or  
Fax +31 (0) 40 2675 222  
In Canada (800)-36-FLUKE or  
Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or  
Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2006 Fluke Corporation. All rights reserved.  
Printed in U.S.A. 11/2006 2793260 D-EN-N Rev A