

Recp Single Surface 30A 125/250V 3P3W BK

UPC: 032664196508

Brand Name: Eaton

Sub Brand: ARROW HART Type: Duplex, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG

Amperage Rating: 20 Amp Voltage Rating: 250 Vac

Material: Nylon Color: Ivory

NEMA Rating: 6-20R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon

Temperature Rating: -20C to 70C (-4F to 158F)

1251

bRecp Single Surface 50A 125V 2P3W BK

UPC: 032664306402

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp

Voltage Rating: 250 Vac

Material: Nylon Color: Brown

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon



Recp Single Surface 50A 250V 2P3W BK

UPC: 032664306501

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp

Voltage Rating: 250 Vac

Material: Nylon Color: Ivory

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon

Temperature Rating: -20C to 70C (-4F to 158F)

1253-BOX

Recp Single Flush 50A 125V 2P3W BK

UPC: 032664306600

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Color: Brown

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon



1254-BOX

Recp Single Flush 50A 250V 2P3W BK

UPC: 032664306709

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Color: Ivory

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon

Temperature Rating: -20C to 70C (-4F to 158F)

1254-BU;1

1254 Recp W/O Zinc Plated Strap BR

UPC: 032664591679

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Color: White

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon



Recp Single Flush 30A 125/250V 3P4W BK

UPC: 032664306808

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3

Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Brown

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 250 vac

Insulation: Nylon Face, Glass Filled Nylon Base Temperature Rating: -20C to 70C (-4F to 158F)



1258-BU/20

1258 Recp W/O Mounting Screws BR

UPC: 032664626876

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3

Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Ivory

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 250 vac Insulation: Nylon Face



1258-BU;3

Recp Sgl Flush 50A125/250V ShortStrap BK

UPC: 032664575501

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3

Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Brown

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac Insulation: Nylon Face



Recp Single Flush 50A 125/250V 3P4W BK

UPC: 032664306907

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3

Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Ivory

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac Insulation: Nylon Face



Recp Single Surface 30A 125/250V 3P3W BK

UPC: 032664196508

Brand Name: Eaton

Sub Brand: ARROW HART Type: Duplex, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG

Amperage Rating: 20 Amp Voltage Rating: 250 Vac

Material: Nylon Color: Ivory

NEMA Rating: 6-20R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon

Temperature Rating: -20C to 70C (-4F to 158F)

1251

bRecp Single Surface 50A 125V 2P3W BK

UPC: 032664306402

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp

Voltage Rating: 250 Vac

Material: Nylon Color: Brown

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon



Recp Single Surface 50A 250V 2P3W BK

UPC: 032664306501

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp

Voltage Rating: 250 Vac

Material: Nylon Color: Ivory

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon

Temperature Rating: -20C to 70C (-4F to 158F)

1253-BOX

Recp Single Flush 50A 125V 2P3W BK

UPC: 032664306600

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Color: Brown

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon



1254-BOX

Recp Single Flush 50A 250V 2P3W BK

UPC: 032664306709

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Color: Ivory

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon

Temperature Rating: -20C to 70C (-4F to 158F)

1254-BU;1

1254 Recp W/O Zinc Plated Strap BR

UPC: 032664591679

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Wiring Type Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Color: White

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height X 1.30 In Length

Environmental Conditions: See Spec Sheet

Dielectric Strength: 2000 V

Insulation: Nylon



Recp Single Flush 30A 125/250V 3P4W BK

UPC: 032664306808

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3

Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Brown

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 250 vac

Insulation: Nylon Face, Glass Filled Nylon Base Temperature Rating: -20C to 70C (-4F to 158F)



1258-BU/20

1258 Recp W/O Mounting Screws BR

UPC: 032664626876

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3

Wire Size: 14 To 10 AWG Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Ivory

NEMA Rating: 6-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 250 vac Insulation: Nylon Face



1258-BU;3

Recp Sgl Flush 50A125/250V ShortStrap BK

UPC: 032664575501

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Brown

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac Insulation: Nylon Face



Recp Single Flush 50A 125/250V 3P4W BK

UPC: 032664306907

Brand Name: Eaton

Sub Brand: ARROW HART Type: Single, Straight Blade

Special Features: Premium Hospital Grade, Wiring Type Back

and Side Wire

Application: Commercial grade

Standard: UL

Number Of Poles: 2 Number Of Wires: 3 Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp Voltage Rating: 125 Vac

Material: Nylon Face, Glass Filled Nylon Base

Color: Ivory

NEMA Rating: 5-15R Mounting: Flush Connection: Screw

Size: 0.82 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac Insulation: Nylon Face