

# Eaton 13101AF1217

Catalog Number: 13101AF1217

Eaton Comet 18mm tubular photoelectric sensor, Forward Viewing, Sensor dist 4 in, 100 mA PNP, 250 mA NPN max DC, NPN/PNP Open coll, 100 mA PNP, 250 mA NPN at 10-30 Vdc, 12 Ft(3.7m) Cable, 10-30 Vdc input, Background Suppression

## General specifications



Product Name	Catalog Number
Eaton Comet 18mm tubular photoelectric sensor	13101AF1217
	UPC
	782113014128
Product Length/Depth	Product Height
0.47 in	2.6 in
Product Width	Product Weight
0.71 in	0.2875 lb
Warranty	Compliances
3 year	Contact Manufacturer

## defaultTaxonomyAttributeLabel

### Contact Rating

100 mA PNP, 250 mA NPN at 10-30 Vdc

### Cable type

Polyvinyl Chloride (PVC)

### Enclosure material

Lens: polycarbonate

Body: structural polyurethane foam

Cable jacket: PVC

### Operating mode

Background suppression

### Connection

12 ft (3.7 m) cable

### Contact configuration

NPN and PNP open collector

### Sensor type

Back ground suppression

### Switch type

Photoelectric

### Input voltage

10-30 Vdc

### LED indicator

Output status: red

### Protection

Auto reset short circuit

### Cord length

144 ft

### Maximum DC current

100 mA PNP, 250 mA NPN

### Operating temperature - max

158 °F

### Operating temperature - min

-40 °F

### Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P,  
NEMA 12, NEMA 13, IP68, IP69K

## Resources

### Catalogs

[Product Range Catalog Sensors – products, basic information, applications](#)

### Specifications and datasheets

[Eaton Specification Sheet - 13101AF1217](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)