

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service Fax: 936-560-

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



1411D6501 Reflex, Self-Contained, 115VAC, 11-Series, Plug-In Rel Eaton Corp

Catalog Number	1411D6501
Manufacturer	Eaton Corp
Description	Eaton E68 Series Integral Sensor Valve Zero Pressure
	Accumulation Sensor, Photoelectric, Right Angle, Structural
	Polyurethane Foam Enclosure, 4 Pin M12 Connector, 18 - 30 VDC
	Input, Polarized Retroreflective
Weight per unit	1.3 (lbs/each)
Product Category	Photoelectric Sensors
Features	
dimensions	3.7900 IN X 7.6500 IN X 5.7000 IN
Descriptions	
Description	REFLEX,SELF-CONTAINED,115VAC,11-SERIES,PLUG-IN REL
extra long description	ETN 1411D-6501 PHOTO SENSOR,REFLEX,
Features	The 11 series are highly configurable photoelectric sensor. The
	sensor operates in the reflex sensing mode with a choice of
	visible or infrared source light. Select one of four different output
	devices to match your control needs. An optional time delay logic
	module is also available.
Long Description	Eaton E68 Series Integral Sensor Valve Zero Pressure
	Accumulation Sensor, Photoelectric, Right Angle, Structural
	Polyurethane Foam enclosure, 4 Pin M12 Connector, 18 - 30 Vdc
Draduct Tupo	input, Polarized Retroreflective Photo Sensor, Reflex, 115vac
Product Type	Photo Sensor, Renex, 115vac
Manufacturer Information	
Brand	Eaton
GTIN	00782113824574
Manufacturers Part Number	1411D6501
UPC	782113824574
Taxonomies, Classifications, and Cate	
Category Description	PROXIMITY SWITCHES AND CORDSETS
Туре	Photoelectric Sensor
Packaging	
Carton	1
Weight Per each	1.2999



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Operating Temperature

Application	
-------------	--

standard

Stationary Mach Equip In Factory - Other Stationary Machinery and Equipment - In Factory
5° to 131°F (-15° to 55°C)
Contact Manufacturer