Specifications

Eaton 170M6760

Catalog Number: 170M6760

Fuse-link, high speed, 630 A, AC 690 V, size 3, 76 x 92 x 139 mm, aR, IEC, UL, single indicator

General specifications

Product Name Eaton Bussmann series high speed square body fuse	**Catalog Number** 170M6760
	UPC 051712792752
EAN 5996516020661	**Product Length/Depth** 168 mm
Product Height 76 mm	**Product Width** 95 mm
Product Weight 959 g	**Warranty** Not Applicable
Compliances CE Marked RoHS Compliant	**Certifications** IEC Rated UL Recognized

Powering Business Worldwide

Product specifications

Type
Fuse

Application
semiconductor protection

Amperage Rating
630 A

Breaking capacity
200 kA

Fuse indicator
Centre fuse status indicator

Insulated metal gripping lugs (IMGL)
No

Utilization category
aR (accompanied semiconductor protection)

Voltage type
AC

Fuse size
3

Rated voltage AC
690 V

Center-to-center distance of connections
114 mm

Current type
AC

Mounting dimension
Other

Class
Class aR

Clearing (I2T)
210000 at 660 V

Watt losses
105 W

Fuse shape
Square body, center bolted tags

Pre arc (I2T)

Resources

Catalogs
eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

170M6760~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

31000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Connection

Blade end x blade end

Construction size

3

Packaging type

Standard

Voltage rating

690 V

Fuse type

US Style

FKE/115 Type K indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia