

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



18122C Uy Gel Filled Splicing Connectors 22-26 Awg *Nsi Industries*

a	
Catalog Number	18122C
Manufacturer	Nsi Industries
Description	Uy Gelfilled Connector 22-26 Awg 100/CLM
Weight per unit	0.1000 (lbs/each)
Product Category	Boxes & Covers
Descriptions	
Description	UY GEL FILLED SPLICING CONNECTORS 22-26 AWG
extra long description	PLATINUM 18122C UY GelFilled Connec
Features	The Telcom Splicing Connectors utilize an insulation displacement contact design for fast, simple, reliable terminations. No wire stripping is required and connectors will accept wire of different gauges. All connectors are Gel filled to provide moisture resistance and inhibit corrosion. For use with solid copper conductors only. Typical uses include Butt Splicing 2 or 3 wires of the same or different gauges. Perfect for pigtail and load coil splice applications. Use the UB connector for tapping onto an ex
Long Description	UY GelFilled Connector 22-26 AWG 100/Clm
Product Type	Uy Gelfilled Connector 22-26 Awg 100/CLM
Special Features	26-22 AWG, 2 wire splice;Max. insulation OD, .060" (1.52mm).;Wires can be of different wire gauges
Manufacturer Information	
Brand	Platinum Tools
GTIN	00849160006817
Manufacturers Part Number	18122C
UPC	849160006817

Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Connectors

Packaging

Carton	1	
Package	4	
Weight Per each	0.1	

Uses, Certifications, and Standards

•	
Application	Cable Installation