



SAFETY DATA SHEET

1. Identification

Product identifier Upside Down Marking Paints - Alert Orange

Other means of identification

Product code 18204

Recommended use Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical 800-521-3168

Assistance

Customer Service 800-272-4620

24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas

Health hazards Carcinogenicity Category 2

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of causing cancer.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a physician/poison center immediately. Do NOT induce vomiting. If exposed or concerned: Get medical attention.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose or store at temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC) Harmful to aquatic life with long lasting effects.

Supplemental information

53.89% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	20 - 30
Calcium carbonate		1317-65-3	10 - 20
n-Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Solvent naphtha (petroleum), light aliph.		64742-89-8	10 - 20
Distillates (petroleum), hydrotreated light		64742-47-8	1 - 5
Titanium dioxide		13463-67-7	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Small Fires: Powder. Water spray. Carbon dioxide (CO2). Dry sand. Large Fires: Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
Propane (CAS 74-98-6)	PEL	15 mg/m3 1800 mg/m3 1000 ppm	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value
n-Butane (CAS 106-97-8)	STEL	1000 ppm
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	10 mg/m3 100 mg/m3	Total
n-Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as nitrile or rubber.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Material name: Upside Down Marking Paints - Alert Orange

1055 Version #: 01 Issue date: 10-01-2013

SDS US

3 / 8

Physical state	Liquid.
Form	Aerosol.
Color	Orange.
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-138.8 °F (-94.9 °C)
Initial boiling point and boiling range	-47.2 °F (-44 °C)
Flash point	-2.2 °F (-19 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.5 %
Flammability limit - upper (%)	10.9 %
Vapor pressure	2221.9 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.77 - 0.85
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	75 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
-----------------------	---

Product	Species	Test Results
Upside Down Marking Paints - Alert Orange		
Acute		
<i>Dermal</i>		
LD50	Rabbit	25990.8555 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	8179.4048 mg/l, 15 Minutes estimated

Product	Species	Test Results
		6351.3516 mg/l, 4 hours estimated
Oral LD50	Rat	90459.0625 mg/kg estimated
Chronic Oral LD50	Mouse	2626.2632 g/kg estimated
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Titanium dioxide (CAS 13463-67-7)		2B Possibly carcinogenic to humans.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.		
Product	Species		Test Results
Upside Down Marking Paints - Alert Orange			
Acute			
Crustacea	EC50	Daphnia	9545.4541 mg/l, 48 hours estimated
Fish	LC50	Fish	15568.5059 mg/l, 96 hours estimated
Components	Species		Test Results
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
Acute			
	EC50	Invertebrate (saltwater)	4720 mg/l, 96 hours
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	1740 mg/l, 96 hours
		Fathead minnow (Pimephales promelas)	45 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octanol / water (log Kow)			
n-Butane	2.89		
Propane	2.36		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal of waste from residues / unused products	This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Empty container can be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Contaminated packaging	Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Not available.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Not available.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
SARA 304 Emergency release notification	Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.
US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance	Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes

Hazard categories Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations**US. New Jersey RTK - Substances: Listed substance**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania RTK - Hazardous Substances

Calcium carbonate (CAS 1317-65-3)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

Titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

Volatile organic compounds (VOC) regulations**EPA**

Aerosol coatings (40 CFR 59, Subpt. E) Compliant

State

Aerosol coatings This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for sale in all 50 states.

Maximum incremental reactivity (MIR) 0.58

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-01-2013
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 1* Flammability: 4 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 4 Instability: 0
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.



SAFETY DATA SHEET

1. Identification

Product identifier Upside Down Marking Paints - Alert Orange

Other means of identification

Product code 18204

Recommended use Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical 800-521-3168

Assistance

Customer Service 800-272-4620

24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas

Health hazards Carcinogenicity Category 2

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of causing cancer.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a physician/poison center immediately. Do NOT induce vomiting. If exposed or concerned: Get medical attention.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose or store at temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC) Harmful to aquatic life with long lasting effects.

Supplemental information

53.89% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	20 - 30
Calcium carbonate		1317-65-3	10 - 20
n-Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Solvent naphtha (petroleum), light aliph.		64742-89-8	10 - 20
Distillates (petroleum), hydrotreated light		64742-47-8	1 - 5
Titanium dioxide		13463-67-7	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Small Fires: Powder. Water spray. Carbon dioxide (CO2). Dry sand. Large Fires: Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
Propane (CAS 74-98-6)	PEL	15 mg/m3 1800 mg/m3 1000 ppm	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value
n-Butane (CAS 106-97-8)	STEL	1000 ppm
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	10 mg/m3 100 mg/m3	Total
n-Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as nitrile or rubber.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Material name: Upside Down Marking Paints - Alert Orange

1055 Version #: 01 Issue date: 10-01-2013

SDS US

3 / 8

Physical state	Liquid.
Form	Aerosol.
Color	Orange.
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-138.8 °F (-94.9 °C)
Initial boiling point and boiling range	-47.2 °F (-44 °C)
Flash point	-2.2 °F (-19 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.5 %
Flammability limit - upper (%)	10.9 %
Vapor pressure	2221.9 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.77 - 0.85
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	75 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
-----------------------	---

Product	Species	Test Results
Upside Down Marking Paints - Alert Orange		
Acute		
<i>Dermal</i>		
LD50	Rabbit	25990.8555 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	8179.4048 mg/l, 15 Minutes estimated

Product	Species	Test Results
		6351.3516 mg/l, 4 hours estimated
Oral LD50	Rat	90459.0625 mg/kg estimated
Chronic Oral LD50	Mouse	2626.2632 g/kg estimated
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Titanium dioxide (CAS 13463-67-7)		2B Possibly carcinogenic to humans.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.		
Product	Species		Test Results
Upside Down Marking Paints - Alert Orange			
Acute			
Crustacea	EC50	Daphnia	9545.4541 mg/l, 48 hours estimated
Fish	LC50	Fish	15568.5059 mg/l, 96 hours estimated
Components	Species		Test Results
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
Acute			
	EC50	Invertebrate (saltwater)	4720 mg/l, 96 hours
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	1740 mg/l, 96 hours
		Fathead minnow (Pimephales promelas)	45 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octanol / water (log Kow)			
n-Butane			2.89
Propane			2.36
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal of waste from residues / unused products	This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Empty container can be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Contaminated packaging	Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Not available.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Not available.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
SARA 304 Emergency release notification	Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.
US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance	Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes

Hazard categories Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations**US. New Jersey RTK - Substances: Listed substance**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania RTK - Hazardous Substances

Calcium carbonate (CAS 1317-65-3)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

Titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

Volatile organic compounds (VOC) regulations**EPA**

Aerosol coatings (40 CFR 59, Subpt. E) Compliant

State

Aerosol coatings This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for sale in all 50 states.

Maximum incremental reactivity (MIR) 0.58

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-01-2013
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 1* Flammability: 4 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 4 Instability: 0
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.