GFCIs

Specification Grade Dead Front GFCI 20A, 125VAC



2085W

Features

- Rated as a 1½ HP motor control switch.
- SafeLock™ Protection: if critical components are damaged and ground fault protection is lost, power to downstream loads is disconnected.
- Feed-thru wiring configuration allows GFCI to protect downstream receptacles.
- Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly.
- Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles.
- Trip indicator light (red LED).
- Side or internal screw-pressure-plate back wire with #10 – #14 AWG solid or stranded copper wire.
- Two back wire holes per terminal.
- Ground screw has a back wire clamp for easy installation.
- 10kA short circuit rating.
- Mounting screws are shipped captive in the device and wall plate for easier installation.
- High-impact-resistant thermoplastic construction.
- Extra-long strap.
- Button colors match the device face.
- Dual-direction test and reset buttons.
- Class A rated GFCI.
- Supplied with matching TP26 nylon wall plate.
- Tri-drive screws.

Specifications

- Supply Voltage: 125VAC, 60 Hz
- Supply Voltage Range: 102-132 VAC
- Trio Threshold: 5± 1mA
- Trip Time: 0.025 sec., nominal per UL Standard
- 20 Amp feed-thru capacity

CATALOG NUMBER	RATING A.	RATING VAC	COLOR	3rd PARTY COMPLIANCE UL943 C22.2 No. 144	3rd PARTY COMPLIANCE UL498 C22.2 No. 42
SPECIFICATION GRADE DEAD FRONT GFCI – 11/2 HP MOTOR CONTROL RATING					
2085I	20	125	Ivory	•	•
2085W	20	125	White	•	•
2085BK	20	125	Black	•	•
2085LA	20	125	Light Almond	•	•

CATALOG NUMBER	COLOR
GFCI EXTENSION RINGS	
1594TPAI	7.0 cu. in. Extension Ring, Ivory
1594TPAW	7.0 cu. in. Extension Ring, White
1594TPA	7.0 cu. in. Extension Ring, Brown
1594TPALA	7.0 cu. in. Extension Ring, Light Almond

1594TPAW EXTENSION RING

All devices listed on this page conform to NEMA WD-1 and WD-6.

DEVICES & WALL PLATES

Color Selection Chart

Devices & Plastic Wall Plate Colors



Ivory | Light Almond | White | Green | Antique Brass | Dark Bronze | Nickel



Black | Blue | Brown | Gray | Orange | Red

See specific device and wall plate catalog charts for particular color availabilities.

Metal Wall Plates

Metal Finish



Aluminum | Brass (Brushed) | Polished Brass | Stainless Steel | Brushed Bronze | Chrome

Custom Metal Wall Plates Paint Finish Colors

Paint Color



Orange | Green | Gray | Yellow | Glossy Black | Brown | White

Primer | Red | Pink | Flat Black | Ivory | Light Almond | Blue

To order custom metal wall plates, see Pages P-40 – P-42.

For additional colors consult factory.

GFCIs

Specification Grade Dead Front GFCI 20A, 125VAC



2085W

Features

- Rated as a 1½ HP motor control switch.
- SafeLock™ Protection: if critical components are damaged and ground fault protection is lost, power to downstream loads is disconnected.
- Feed-thru wiring configuration allows GFCI to protect downstream receptacles.
- Prevents line-load reversal miswire: no power to the face or downstream receptacles if wired incorrectly.
- Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles.
- Trip indicator light (red LED).
- Side or internal screw-pressure-plate back wire with #10 – #14 AWG solid or stranded copper wire.
- Two back wire holes per terminal.
- Ground screw has a back wire clamp for easy installation.
- 10kA short circuit rating.
- Mounting screws are shipped captive in the device and wall plate for easier installation.
- High-impact-resistant thermoplastic construction.
- Extra-long strap.
- Button colors match the device face.
- Dual-direction test and reset buttons.
- Class A rated GFCI.
- Supplied with matching TP26 nylon wall plate.
- Tri-drive screws.

Specifications

- Supply Voltage: 125VAC, 60 Hz
- Supply Voltage Range: 102-132 VAC
- Trio Threshold: 5± 1mA
- Trip Time: 0.025 sec., nominal per UL Standard
- 20 Amp feed-thru capacity

CATALOG NUMBER	RATING A.	RATING VAC	COLOR	3rd PARTY COMPLIANCE UL943 C22.2 No. 144	3rd PARTY COMPLIANCE UL498 C22.2 No. 42
SPECIFICATION GRADE DEAD FRONT GFCI – 11/2 HP MOTOR CONTROL RATING					
2085I	20	125	Ivory	•	•
2085W	20	125	White	•	•
2085BK	20	125	Black	•	•
2085LA	20	125	Light Almond	•	•

CATALOG NUMBER	COLOR
GFCI EXTENSION RINGS	
1594TPAI	7.0 cu. in. Extension Ring, Ivory
1594TPAW	7.0 cu. in. Extension Ring, White
1594TPA	7.0 cu. in. Extension Ring, Brown
1594TPALA	7.0 cu. in. Extension Ring, Light Almond

1594TPAW EXTENSION RING

All devices listed on this page conform to NEMA WD-1 and WD-6.

DEVICES & WALL PLATES

Color Selection Chart

Devices & Plastic Wall Plate Colors



Ivory | Light Almond | White | Green | Antique Brass | Dark Bronze | Nickel



Black | Blue | Brown | Gray | Orange | Red

See specific device and wall plate catalog charts for particular color availabilities.

Metal Wall Plates

Metal Finish



Aluminum | Brass (Brushed) | Polished Brass | Stainless Steel | Brushed Bronze | Chrome

Custom Metal Wall Plates Paint Finish Colors

Paint Color



Orange | Green | Gray | Yellow | Glossy Black | Brown | White

Primer | Red | Pink | Flat Black | Ivory | Light Almond | Blue

To order custom metal wall plates, see Pages P-40 – P-42.

For additional colors consult factory.