


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





2097TR Radiant Self Test TR Gfci 20A 125V BR

Pass & Seymour/Legrand

| Catalog Number | 2097TR |
|------------------|--|
| Manufacturer | Pass & Seymour/Legrand |
| Description | 20A 125V Self-Test Tamper-Resistant Gfci Brown |
| Weight per unit | 0.2750 (lbs/each) |
| Product Category | |

Features

| actuator | Control Circuit |
|------------------|---------------------|
| amperage rating | 20 |
| connection | Back and side wire |
| interrupt rating | 4 to 6 mA |
| Material | Thermoplatic |
| Poles | 2 |
| trip range | 4 to 6 mA |
| Trip Type | .025 Second Nominal |
| Voltage Rating | 125 |

Dimensions and Weight

| Height | 4.2 |
|--------|------|
| Length | 1.03 |
| Width | 1.73 |

Descriptions

| Description | RADIANT SELF TEST TR GFCI 20A 125V BR |
|------------------------|---|
| extra long description | P&S 2097TR RADIANT SELF TEST TR GFC |
| Long Description | 20A 125V Self-Test Tamper-Resistant GFCI Brown |
| Product Type | Radiant Self Test TR Gfci 20A 125V BR |
| Special Features | Pass & Seymour invented the GFCI receptacle, and at Legrand, we're constantly reinventing it to ensure the highest level of safety possible. From the most advanced self-testing device to audible alarms to nightlight combos, we're continuously resetting the bar on GFCI innovation and safety. |

Manufacturer Information

| Brand | Pass & Seymour |
|---------------------------|----------------|
| GTIN | 00785007036152 |
| Manufacturers Part Number | 2097TR |
| UPC | 785007036152 |

Taxonomies, Classifications, and Categories

| Category Description | Residential GFCI devices |
|----------------------|---|
| Type | Specification GradeTamper-Resistant 20A Self-Test Duplex GFCI |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging |
|-----------|
|-----------|

| Carton | 1 | |
|-----------------|-------|--|
| Package | 10 | |
| Weight Per each | 0.275 | |

Uses, Certifications, and Standards

| Application | Commercial/Residential |
|--------------------------|------------------------|
| environmental conditions | 95% Humidity, UL 94 V2 |
| Frequency Rating | 60 Hz |
| Operating Temperature | -35°C to +66°C |
| standard | cULus, UL Listed, FSUL |