

0

0

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| 2263 Clear Sleeve For F96 \$<br>Appleton/Oz Gedney |   |
|--|---|
| Catalog Number                                     | 2263  |
| Manufacturer                                       | Appleton/Oz Gedney  |
| Description  | Clear Protect-O-Sleeves For Size T-12 Fluorescent Tubes,<br>Reusable High Tensile, Polycarbonate Sleeve Encasing, Insulate<br>Lamps Up to 20 Deg F/-6 Deg C, Can Be Used For Lamps Up to<br>800 Milliamps, Ambient Temperature Up to 100 Deg F, Lamp<br>Type F-96, Length 96 In |
| Weight per unit                                    | 0.3700 (lbs/each)   |
| Product Category                                   | Lighting Accessories  |
| Features   |   |
| Material   | Polycarbonate   |
| Material, Color, and Finish                        |   |
| Color  | Clear   |
| Descriptions                                       |   |
| Description  | CLEAR SLEEVE FOR F96 \$   |
| extra long description                             | MCG 2263 SLEEVE F96 LAMP T12 CLEAR  |
| Long Description                                   | Clear Protect-O-Sleeves for size T-12 fluorescent tubes, reusable<br>high tensile, polycarbonate sleeve encasing, insulate lamps up to<br>20 DEG F/-6 DEG C, can be used for lamps up to 800 milliamps,<br>ambient temperature up to 100 DEG F, Lamp TYPE F-96, length<br>96 IN |
| Product Type                                       | Sleeve F96 Lamp T12 Clear   |
| Special Features                                   | With 2 Caps For T12 Diameter Lamp, Lamp Type F96, Lamp<br>Length 96 IN  |
| Manufacturer Information                           |   |
| Brand  | Appleton/Oz Gedney  |
| GTIN   | 00036283290340  |
| Manufacturers Part Number                          | 2263  |
| UPC  | 036283290340  |
| Taxonomies, Classifications, and Carry Type        |   |
|  |   |
| Packaging<br>Carton                                | 1   |
| Weight Per each                                    | 0.37  |
| Uses, Certifications, and Standards                |   |
| Application  | Museums, Department Stores, and Art Galleries   |