

## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

242084XS Encl 24X20X7 N4X SS Encl Cooper B-Line/Cable Tray

242084XS
Cooper B-Line/Cable Tray
Eaton B-Line Series Wall Mounted Panel Enclosure, 24" Height, 8
Length, 20" Width, Nema 4X, Hinged Cover, 4XS Enclosure, Wall
Mount, Medium Single Door, External Mounting Feet, 304
Stainless Steel, Seamless Poured In-Place Gasket
41.1 (lbs/each)
Nema Types 4 & 4X Metallic Enc
8.0000 IN X 20.0000 IN X 24.0000 IN
304 Stainless Steel
Wall
Gray
20.00 In Width X 8.00 In Depth X 24.00 In Height
ENCL 24X20X7 N4X SS ENCL
B-LINE 24208-4XS TYPE 4X SSL SGL-DO
Eaton's B-Line series wall mounted panel enclosures provide
reliable environmental protection and are used to house electrical controls and instruments.
Eaton B-Line series wall mounted panel enclosure, 24" height, 8"
length, 20" width, NEMA 4X, Hinged cover, 4XS enclosure, Wall
mount, Medium single door, External mounting feet, 304
stainless steel, Seamless poured in-place gasket
Type 4X SSL SGL-Door Enc, 24X20X8
Stainless door clamps
Eaton
00782051880021
24208-4XS
782051880021



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	
Weight Per each	41.101
Uses, Certifications, and Standards	
Application	Other IT and Datacom - IT and Datacomm - OtherCommercial / Institutional Buildings / Structures - Critical PowerUtility - Substations, Utility Transmission and DistributionCommercial / Institutional Buildings / Structures - Power Distribution and ControlsGeneration - Renewable Energy - Alternative EnergyDatacenters - IT Space: CI and Hyper ConvergedCommercial / Institutional Buildings / Structures - Safety and Security SystemsCommercial / Institutional Buildings / Structures - Building Automation and Monit
Mounting	EXTERNAL FEET, WÄLL
nema rating	4X
standard	NEMA,UL 50,CSA C22.2.