
Globe Lamps G25, G30, G40 Series Specifications

SpringLamp® Compact Fluorescent, NPF

8,000 Hours average rated life

Catalog Number

Notes | Type




Applications:

- Use anywhere a standard incandescent is used.

Replaces Incandescent for:

- ✚ Vanity Strips
- ✚ Table Lamps
- ✚ Closet Lights
- ✚ Ceiling Fixtures
- ✚ Sconces




Special Application Options: (Ordering Suffix)

- 3100K (31K)
- 3500K (35K)
- 4100K (41K)
- 5500K (55K)
- 6500K (65K)

Features and Benefits

- Long life CFL, 8,000 hour average rated life
- Amalgam technology- provides cooler operating temperatures for consistent performance in any position
- No lead glass- Better lumen maintenance over life of bulb
- 2700˚K color temperature closest to incandescent light
- Medium base or candelabra base available
- Replace less often, ideal for hard to reach places
- Quick run-up time
- Medium base and compact height fits anywhere a standard incandescent fits
- Instant start, flicker free
- End of Life logic guards against violent failures
- Quickstart technology - fast run up time



G25 G30 G40

Specifications (at full brightness)

End of Life Protection	Yes
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	8,000 Hours
Color Temperature	2700ºK
Color Rendering Index	82
Minimum Starting Temperature	-20ºF, -29ºC
Maximum Operating Temperature	160ºF, 71ºC
U.L. / C.U.L. Listed	Yes – E149698
FCC Compliance	Part 18, Subpart C
Lamp Operating Frequency	45 KHZ
Max. Open Circuit Voltage	600V
Lamp Current Crest Factor	<1.60
Total Harmonic Distortion	<150%
High Power Factor Rated	>.50

Special Notes

- UL approved for wet location in Base Up position only. Base Up position is defined as screw base in a 12:00 position. Any other base position must be in a UL approved weatherproof fixture.

Item #	Wattage	Incandescent Wattage Comparison	Initial Lumens	Input Line Current	M.O.L. (inches)	Diameter (inches)	Base Type
1G2504	4	25	250	.07A	4.2	3.1	E26
1G2509	9	40	495	.15A	4.2	3.1	E26
1G2509C	9	40	495	.15A	4.2	3.1	E12
2G2514	14	60	800	.23A	4.7	3.1	E26
1G3009	9	40	495	.15A	5.0	3.7	E26
1G3014	14	60	800	.23A	5.0	3.6	E26
1G3019	19	75	950	.32A	4.9	3.7	E26
1G3023	23	100	1400	.38A	5.9	3.6	E26
1G4014	14	60	800	.23A	6.8	5.0	E26
1G4019	19	75	950	.30A	6.8	5.0	E26
1G4023	23	100	1300	.38A	6.8	5.2	E26

For the most up-to-date specs, please visit www.tcpi.com

Warranties and Certifications:

c UL us

ISO 9002 CERTIFIED

12 MONTH WARRANTY

TCP reserves the right to void the warranty for any mis-application of these products.

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 1-800-324-1496 | tcpi.com

©TCP JUL 2016/WF12662

ENERGY STAR PARTNER


Globe Lamps G25, G30, G40 Series Specifications

SpringLamp® Compact Fluorescent, NPF

8,000 Hours average rated life

Catalog Number

Notes | Type




Applications:

- Use anywhere a standard incandescent is used.

Replaces Incandescent for:

- ✚ Vanity Strips
- ✚ Table Lamps
- ✚ Closet Lights
- ✚ Ceiling Fixtures
- ✚ Sconces




Special Application Options: (Ordering Suffix)

- 3100K (31K)
- 3500K (35K)
- 4100K (41K)
- 5500K (55K)
- 6500K (65K)

Features and Benefits

- Long life CFL, 8,000 hour average rated life
- Amalgam technology- provides cooler operating temperatures for consistent performance in any position
- No lead glass- Better lumen maintenance over life of bulb
- 2700˚K color temperature closest to incandescent light
- Medium base or candelabra base available
- Replace less often, ideal for hard to reach places
- Quick run-up time
- Medium base and compact height fits anywhere a standard incandescent fits
- Instant start, flicker free
- End of Life logic guards against violent failures
- Quickstart technology - fast run up time



G25 G30 G40

Specifications (at full brightness)

End of Life Protection	Yes
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	8,000 Hours
Color Temperature	2700ºK
Color Rendering Index	82
Minimum Starting Temperature	-20ºF, -29ºC
Maximum Operating Temperature	160ºF, 71ºC
U.L. / C.U.L. Listed	Yes – E149698
FCC Compliance	Part 18, Subpart C
Lamp Operating Frequency	45 KHZ
Max. Open Circuit Voltage	600V
Lamp Current Crest Factor	<1.60
Total Harmonic Distortion	<150%
High Power Factor Rated	>.50

Special Notes

- UL approved for wet location in Base Up position only. Base Up position is defined as screw base in a 12:00 position. Any other base position must be in a UL approved weatherproof fixture.

Item #	Wattage	Incandescent Wattage Comparison	Initial Lumens	Input Line Current	M.O.L. (inches)	Diameter (inches)	Base Type
1G2504	4	25	250	.07A	4.2	3.1	E26
1G2509	9	40	495	.15A	4.2	3.1	E26
1G2509C	9	40	495	.15A	4.2	3.1	E12
2G2514	14	60	800	.23A	4.7	3.1	E26
1G3009	9	40	495	.15A	5.0	3.7	E26
1G3014	14	60	800	.23A	5.0	3.6	E26
1G3019	19	75	950	.32A	4.9	3.7	E26
1G3023	23	100	1400	.38A	5.9	3.6	E26
1G4014	14	60	800	.23A	6.8	5.0	E26
1G4019	19	75	950	.30A	6.8	5.0	E26
1G4023	23	100	1300	.38A	6.8	5.2	E26

For the most up-to-date specs, please visit www.tcpi.com

Warranties and Certifications:

c UL us

ISO 9002 CERTIFIED

12 MONTH WARRANTY

TCP reserves the right to void the warranty for any mis-application of these products.

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 1-800-324-1496 | tcpi.com

©TCP JUL 2016/WF12662

ENERGY STAR PARTNER