



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



30030 Noalox (8 Oz. Bottle)

Ideal

| | |
|------------------|---|
| Catalog Number | 30030 |
| Manufacturer | Ideal |
| Description | Anti-Oxidant Compound, 8 Oz Squeeze Bottle, Petroleum Base, 1.04 Specific Gravity, 310 °F Flash Point, 0.6 LB |
| Weight per unit | 0.6000 (lbs/each) |
| Product Category | Paint, Chemicals, Etc. |

Features

| | |
|------------------|------|
| specific gravity | 1.04 |
|------------------|------|

Dimensions and Weight

| | |
|------|---------------------|
| Size | 8 OZ Squeeze Bottle |
|------|---------------------|

Descriptions

| | |
|-------------|-----------------------|
| Description | NOALOX (8 OZ. BOTTLE) |
|-------------|-----------------------|

| | |
|------------------------|-------------------------------------|
| extra long description | IDEAL 30-030 NOALOX ANTI-OXIDANT 80 |
|------------------------|-------------------------------------|

| | |
|----------|---|
| Features | IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-type wire connectors. |
|----------|---|

| | |
|------------------|---|
| Special Features | Anti-oxidant and anti-seizing compound improves efficiency and service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service life of aluminum ele |
|------------------|---|

Manufacturer Information

| | |
|-------|-------|
| Brand | Ideal |
|-------|-------|

| | |
|------|----------------|
| GTIN | 00783250300303 |
|------|----------------|

| | |
|-----|--------------|
| UPC | 783250300303 |
|-----|--------------|

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------------|
| Category Description | WIRE LUBE, MARKERS, & TIES |
|----------------------|----------------------------|

| | |
|------|-----------------------|
| Type | Anti-Oxidant Compound |
|------|-----------------------|



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|-----|
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.6 |

Uses, Certifications, and Standards

| | |
|----------|-----------|
| standard | UL Listed |
|----------|-----------|