

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Product Type

Special Features

300GCX120 300GCX Selectone Hazloc Speaker

300GCX120		
Federal Signal Corp.		
Selectone 15 Watt Amplified Speaker, Hazardous Location, 120VAC, Gray - Available In 24VAC/DC, 120VAC and 240VAC. Reliable, Solid-State Circuitry. Digital Signal Amplification. Fused Input and Output. Built-In Gain Control, Adjustable Between 0 Dba to 110 Dba At 10 Feet (0 Dba to 120 Dba At 1 Meter). Cast Copper Free Aluminum Housing, Spun Aluminum Projector. Type 4X, IP66 Enclosure. IP69K Compliant. Indoor/Outdoor Use. CSFM Approved. UI and Cul Listed For Class I, Division 2, Groups A, B, C and D & Class		
6.5 (lbs/each)		
Sound & Audio Systems		
12.4 H x 7.9 W x 8.5 D		
Die-Cast Aluminum		
0.20		
120VAC 50-60Hz		
15		
Gray		
300GCX SELECTONE HAZLOC SPEAKER		
FED-SIG 300GCX-120 15W AMPLIFIED SP		
SelecTone 15 Watt Amplified Speaker, Hazardous Location,		
120VAC, Gray - Available in 24VAC/DC, 120VAC and 240VAC.		
Reliable, solid-state circuitry. Digital signal amplification. Fused		
input and output. Built-in gain control, adjustable between 0 dBa to 110 dBa at 10 feet (0 dBa to 120 dBa at 1 meter). Cast copper		
free aluminum housing, spun aluminum projector. Type 4X, IP66 enclosure. IP69K compliant. Indoor/outdoor use. CSFM Approved. UL and cUL Listed for Class I, Division 2, Groups A, B, C and D & Class		

15W Amplified Speaker 120V Haz Loc

Digital Signal Amplification



Type

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	Federal Signal	
GTIN	00782979200376	
Manufacturers Part Number	300GCX-120	
UPC	782979200376	

Hazardous Location Amplified Speaker

Taxonomies, Classifications, and Categories

Packaging		
Carton	1	
Weight Per each	6.5	

Uses, Certifications, and Standards

Application	Indoor/Outdoor
Enclosure	Type 4X, IP66, IP69K
Mounting	
Operating Temperature	-67 to 150
	UL Listed/cUL Listed/CSFM Approved