ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
7604 Gateway Blvd
77521-0000, TX Baytown
Phone: 832-514-7819
Fax: 832-514-7820



# 30452 Wing-Nut Wire Connector, 452 Red, 100/Box

*Ideal*

| | |
|---|---|
| Catalog Number | 30452 |
| Manufacturer | Ideal |
| Description | Twist-On Wingnut, Red Insulation Color, +221 °F Operating Temperature, 1 to 6 Conductors, 600 V Ac, 0.01 LB |
| Weight per unit | 0.7100 (lbs/each) |
| Product Category | Electrical Fixture Conn ( Nuts |

## Features

| | |
|---|---|
| Material | Flame-retardant polypropelene shell |
| media | Yes |
| Voltage Rating | 600 |

## Material, Color, and Finish

| | |
|---|---|
| Color | Red |

## Descriptions

| | |
|---|---|
| Description | WING-NUT WIRE CONNECTOR, 452 RED, 100/BOX |
| extra long description | IDEAL 30-452 WINGNUT 452 RED, 100 B |
| Features | Largest range in the Industry - from 2 #18 to up 4 #10High-leverage, contoured wing provides superior torque on every twistWide range, live-action spring handles small combinations and expands to accommodate large combinations as you need itCopolymer shell expands for smooth, progressive tightening providing dependable connectionsRemovable for repeat usage on same size or larger combinationsMore power with every twist.The Wing-Nut Wire Connector provides an easy, secure grip when connecting a wide range of |

## Manufacturer Information

| | |
|---|---|
| Brand | Ideal |
| GTIN | 00783250304523 |
| UPC | 783250304523 |

## Taxonomies, Classifications, and Categories

| | |
|---|---|
| Category Description | WIRE NUTS |
| Type | Twist-On |

## Availability

| | |
|---|---|
| minimum qty | 100 |

## Packaging

| | |
|---|---|
| Carton | 100 |
| Package | 1000 |
| Weight Per each | 0.71 |

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
7604 Gateway Blvd
77521-0000, TX Baytown
Phone: 832-514-7819
Fax: 832-514-7820

## Uses, Certifications, and Standards

| | |
|---|---|
| Application | Insulating or Joining 2 or more conductors |
| environmental conditions | Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F) |
| standard | CSA Certified to C22.2 #188, UL Listed to 486C, complies with Federal Specification W-S-610E, RoHS Compliant |