

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



35419 Wrench, Combo Ratchet 3/4" *Greenlee Textron*

Catalog Number	35419
Manufacturer	Greenlee Textron
Description	Combination Ratcheting Wrench, 3/4". Compact Reversible Switch Allows A 15° Offset Of The Box End For Clearance Of Obstacles. 5° Ratcheting Design For Versatility and Ease Of Use In Tight Spaces. Polished Chrome Finish For Superior Corrosion Resistance. Precision Heads For Accurate Fastener Fit. Hardened For Durability and Longer Life. Exceeds Asme/Ansi Specifications. Lifetime Limited Warranty. Note: This Is Not An Insulated Tool.
Weight per unit	0.5850 (lbs/each)
Product Category	Pliers, Wrenches, Saw, Pouches

Features

Drive Size 3/4 IN

Material, Color, and Finish

Finish POLISHED CHROME

Dimensions and Weight

9-3/4 IN (24.800 CM) Overall Length

Descriptions

Description	WRENCH,COMBO RATCHET 3/4"
extra long description	GRN 0354-19 WRENCH,COMBO RATCHET 3/
Long Description	Combination Ratcheting Wrench, 3/4". Compact reversible switch allows a 15° offset of the box end for clearance of obstacles. 5° ratcheting design for versatility and ease of use in tight spaces. Polished chrome finish for superior corrosion resistance. Precision heads for accurate fastener fit. Hardened for durability and longer life. Exceeds ASME/ANSI specifications. Lifetime limited warranty. Note: This is not an insulated tool.
Product Type	Wrench, Combo Ratchet 3/4"

Manufacturer Information

Brand	GREENLEE	
GTIN	00783310892694	
Manufacturers Part Number	0354-19	
UPC	783310892694	

Taxonomies, Classifications, and Categories

Category Description	HAND TOOLS
Туре	Standard, Combination



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight	0.530 LB (0.240 KG)
Weight Per each	0.585
Uses, Certifications, and Standards	
Application	For Versatility And Ease Of Use In Tight Spaces And Accurate
	Fastener Fit

ASME/ANSI