# **3M**

# Scotch<sup>®</sup> Industrial Box Sealing Tape

371

**Available Sizes** 

Standard Widths:

Size (ID): Lengths:

Product Description	Scotch® Box Sealing Tape 371 is an industrial packaging tape used for box sealing, splicing, recouperage and other packaging applications. This product has a conformable backing and a consistent pressure sensitive hot melt synthetic rubber adhesive system.			
Construction	Backing Adhesive Cold		Colors	
	Biaxially oriented polypropylene		Blue, clear, green, orange, red, tan, yellow, and white	
Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.  ASTM Test Method			
	Adhesion to Steel:	40 oz./in. width (43.7 N/100 mm wid	th) D-3330	
	Tensile Strength:  Machine Direction:  Cross Direction:	22 lbs./in. width (385 N/100 mm wid 44 lbs./in. width (771 N/100 mm wid	•	
	Elongation at Break:	160%	D-3759	
	Tape Thickness:	1.8 mil (0.045 mm)	D-3652	
	Holding Power:	3,500+ minutes	D-3654	
Features	Adheres instantly to a variety of surfaces.			
	Edge tear and split resistance.			
	Good adhesion to fiberboard.			
	<ul> <li>Roll to roll consistency increases productivity for improved unit costs.</li> </ul>			
	<ul> <li>Roll to roll consistency</li> </ul>	increases productivity for improved	unit costs.	

36 mm, 42 mm, 48 mm, 72 mm Core

50 m, 100 m, 914 m, 1500 m, 1828 m

# Scotch<sup>®</sup> Industrial Box Sealing Tape

371

# **Application Techniques**

An extensive line of application equipment including hand held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® Box Sealing Tape 371 is most easily accomplished at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, Scotch® Tape 371 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

# **Storage Conditions**

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.

# **Shelf Life**

To obtain best performance, use this product within 18 months from date of manufacture.

## **Technical Information**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

## **Product Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

# Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

# **Limitation of Liability**

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.



# **3M**

# Scotch<sup>®</sup> Industrial Box Sealing Tape

371

**Available Sizes** 

Standard Widths:

Size (ID): Lengths:

Product Description	Scotch® Box Sealing Tape 371 is an industrial packaging tape used for box sealing, splicing, recouperage and other packaging applications. This product has a conformable backing and a consistent pressure sensitive hot melt synthetic rubber adhesive system.			
Construction	Backing Adhesive Cold		Colors	
	Biaxially oriented polypropylene		Blue, clear, green, orange, red, tan, yellow, and white	
Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.  ASTM Test Method			
	Adhesion to Steel:	40 oz./in. width (43.7 N/100 mm wid	th) D-3330	
	Tensile Strength:  Machine Direction:  Cross Direction:	22 lbs./in. width (385 N/100 mm wid 44 lbs./in. width (771 N/100 mm wid	•	
	Elongation at Break:	160%	D-3759	
	Tape Thickness:	1.8 mil (0.045 mm)	D-3652	
	Holding Power:	3,500+ minutes	D-3654	
Features	Adheres instantly to a variety of surfaces.			
	Edge tear and split resistance.			
	Good adhesion to fiberboard.			
	<ul> <li>Roll to roll consistency increases productivity for improved unit costs.</li> </ul>			
	<ul> <li>Roll to roll consistency</li> </ul>	increases productivity for improved	unit costs.	

36 mm, 42 mm, 48 mm, 72 mm Core

50 m, 100 m, 914 m, 1500 m, 1828 m

# Scotch<sup>®</sup> Industrial Box Sealing Tape

371

# **Application Techniques**

An extensive line of application equipment including hand held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® Box Sealing Tape 371 is most easily accomplished at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, Scotch® Tape 371 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

# **Storage Conditions**

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.

# **Shelf Life**

To obtain best performance, use this product within 18 months from date of manufacture.

## **Technical Information**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

## **Product Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

# Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

# **Limitation of Liability**

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.

