

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **390 4" Malleable Insulated Grounding Bushing** *Bridgeport Fittings*

Catalog Number	390
Manufacturer Description	Bridgeport Fittings Bushing, Insulated, Grounding, Malleable Iron, Size 4 Inch, 14-1/0
Description	Lug
Weight per unit	1.0 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
Features	
Material	Malleable Iron
media	Yes
Material, Color, and Finish	
Color	Grey with Black Insulator
Finish	Zinc Electroplated
Dimensions and Weight	
Size	4
Descriptions	
Description	4" MALLEABLE INSULATED GROUNDING BUSHING
extra long description	BPT 390 4" GRD.BUSH.INS. 14-1/0 MAL
Long Description	Bushing, Insulated, Grounding, Malleable Iron, Size 4 Inch, 14-1/0 Lug
Product Type	4" GRD.Bush.Ins. 14-1/0 Mall
Special Features	Grounding Lug Wire Capacity #14 - #1/0
Manufacturer Information	
Brand	Bridgeport
GTIN	00781747003904
UPC	781747003904
Taxonomies, Classifications, and	d Categories
Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Туре	BUSHING
Trade Size	
Trade Size	4
Packaging	
Carton	20
Weight Per each	1



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum allog 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated
standard	105 degree C. cULus
Temperature Rating	150?°C