



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



3X4 3X4 RGD Nip *Robroy/Ecn Korns*

Catalog Number	3X4
Manufacturer	Robroy/Ecn Korns
Description	Conduit Nipple, 4 Inch; Rigid Conduit Used On; UI 6, Csa C22.2 Approval; 10 Per Carton Standard Package; 3 Inch Trade Size; Robroy. Brand; Applicable Standard Ansi C80.1, Naed, Nema, Nemra, NMG; Finish Galvanized; Galnip Model
Weight per unit	1.8 (lbs/each)
Product Category	Steel

Dimensions and Weight

Length	4 INCH
--------	--------

Descriptions

Additional Information	APPLICABLE STANDARD ANSI C80.1, NAED, NEMA, NEMRA, NMG; FINISH GALVANIZED
Commodity Description	ELBOWS-COUPINGS-NIPPLES - STEEL
Description	3X4 RGD NIP
extra long description	MALE THREADED TYPE; HOT DIP GALVANIZED STEEL MATERIAL; 4 INCH; IMC/RIGID CONDUIT USED ON; UL (CANADA AND US), UL 6, CSA C22.1/C22.2, NOM APPROVAL; 3.5 INCH DIAMETER; 10 PER CARTON STANDARD PACKAGE; 3 INCH TRADE SIZE; APPLICATION INDOOR/OUTDOOR, HAZARDOUS AND NON-HAZARDOUS LOCATION; APPLICABLE STANDARD ANSI/NFPA 70, NEC 344, ISO 9001; GALNIP MODEL
Long Description	CONDUIT NIPPLE, 4 INCH; RIGID CONDUIT USED ON; UL 6, CSA C22.2 APPROVAL; 10 PER CARTON STANDARD PACKAGE; 3 INCH TRADE SIZE; ROBROY. BRAND; APPLICABLE STANDARD ANSI C80.1, NAED, NEMA, NEMRA, NMG; FINISH GALVANIZED; GALNIP MODEL
Product Type	Conduit Nipple

Manufacturer Information

Brand	EC-KORNS
GTIN	00784011006144
Manufacturers Part Number	GALNIP3X4
Model	GALNIP
UPC	784011006144

Taxonomies, Classifications, and Categories

Category Description	RIGID NIPPLES
----------------------	---------------

Trade Size

Trade Size	3 INCH
------------	--------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Package	10
Standard Package	10 PER CARTON
Weight Per each	1.75

Uses, Certifications, and Standards

Approval	UL 6, CSA C22.2
Used On	RIGID CONDUIT