



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



40SR 4/0 Al/Cu Mechanical Butt Splice

Nsi Industries

Catalog Number	40SR
Manufacturer	Nsi Industries
Description	Aluminum Splicer Reducer 4/0-6 Awg Aluminum Splicer Reducers Are Used For Splicing Two Copper or Aluminum Wires Of Equal or Different Sizes. Made Of 6061T-6 Aluminum Alloy. Electro-Tin Plated For Low Contact Resistance. Suitable For Use With Both Copper and Aluminum Conductors. Rated 600 Volts (2000V Max. Per UL486B). UI 486A/B Listed. Temperature Rating 90 Degrees C.
Weight per unit	0.1100 (lbs/each)
Product Category	Splicing & Terminating Kits

Features

Voltage Rating	600 V
Warranty	1 YEAR

Descriptions

Description	4/0 AL/CU MECHANICAL BUTT SPLICE
extra long description	NSI 4/0SR AL/CU CONN 4-14 AWG 7 HOL
Features	Aluminum Splicer Reducer 4/0-6 AWG Aluminum Splicer Reducers are used for splicing two copper or aluminum wires of equal or different sizes. Made of 6061T-6 aluminum alloy. Electro-tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600 volts (2000V max. per UL486B). UL 486A/B Listed. Temperature rating 90 degrees C.
Long Description	Aluminum Splicer Reducer 4/0-6 AWG Aluminum Splicer Reducers are used for splicing two copper or aluminum wires of equal or different sizes. Made of 6061T-6 aluminum alloy. Electro-tin plated for low contact resistance. Suitable for use with both copper and aluminum conductors. Rated 600 volts (2000V max. per UL486B). UL 486A/B Listed. Temperature rating 90 degrees C.
Product Type	Al/Cu Conn 4-14 Awg 7 Holes 5 Circuits
Special Features	4/0-6 AWG - Dual Rated - 24 Pack

Manufacturer Information

Brand	NSi
GTIN	00662381002327
Manufacturers Part Number	4/0SR
UPC	662381002327



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Type	Splicer-Reducers

Packaging

Carton	1
Package	24
Weight Per each	0.11

Uses, Certifications, and Standards

Application	Wire Spicing
standard	cULus