



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 4156DC 1/2" X2 Trans Emt/CBL CPLG

*Nsi Industries*

|                  |  |
|------------------|--|
| Catalog Number   | 4156DC   |
| Manufacturer     | Nsi Industries   |
| Description      | Mighty-Merge® Transition Fittings, 1/2" Emt to Duplex Ac/MC Coupling |
| Weight per unit  | 0.2730 (lbs/each)  |
| Product Category | Die Cast Set Screw Emt to Flex                                       |

### Features

|       |     |
|-------|-----|
| media | Yes |
|-------|-----|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 1/2" X2 TRANS EMT/CBL CPLG   |
| extra long description | BPT 4156-DC 1/2 IN X2 Trans Emt/Cab  |
| Long Description       | Mighty-Merge® Transition Fittings, 1/2" EMT to Duplex AC/MC Coupling                 |
| Product Type           | 1/2 In X2 Trans Emt/Cable CPLG, Box Of 10  |
| Special Features       | Set Screw type transition fitting ideal for commercial and institutional facilities. |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | Bridgeport     |
| GTIN                      | 00781747941565 |
| Manufacturers Part Number | 4156-DC        |
| UPC                       | 781747941565   |

### Taxonomies, Classifications, and Categories

|                      |                          |
|----------------------|--------------------------|
| Category Description | Fuses & Fuse Accessories |
| Type                 | COUPLING                 |

### Trade Size

|            |     |
|------------|-----|
| Trade Size | 0.5 |
|------------|-----|

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 10    |
| Package         | 40    |
| Weight Per each | 0.273 |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

The 4156-DC is used to securely join 1/2" EMT to two 14/2 to 10/3 (.43" to .61" Diameter) AC/MC/MCI-A/HCF/HCFMCI-A or 3/8" flexible metal conduit. These fittings provide a huge labor savings, compared to the traditional junction box or fitting assembly installation. When using AC/MC/FMC cable simply remove the armor and expose the conductors to the desired length needed to reach the device box or enclosure. The inspection holes will provide a visual end stop for the cable or flex conduit. The use of anti s

standard

cETLus