

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



48005193 8" 10/14 Tpi Sawzall Blades 5PK *Milwaukee Electric Tool*

| Catalog Number | 48005193 |
|---------------------------|--|
| Manufacturer | Milwaukee Electric Tool |
| Description | Milwaukee® Designs and Manufactures Sawzall® Blades For The |
| · | Toughest Professional Applications. Material, Blade Geometry and Heat Treating Are Designed to Maximize General Purpose |
| | Cutting Performance. |
| Weight per unit | 0.3150 (lbs/each) |
| Product Category | Bits, Parts, Accessories |
| Features | |
| Blade Length | 8.0 |
| Blade Thickness | 0.035 |
| Teeth per Inch | 10/14 |
| Dimensions and Weight | |
| Length | 8 |
| Thickness | 035 |
| Width | 0.625 |
| Descriptions | |
| Description | 8" 10/14 TPI SAWZALL BLADES 5PK |
| extra long description | MILW 48-00-5193 Blade 10/14TPI 8" |
| Features | 8 in. 10/14 TPI SAWZALL® Blades 5PK |
| Long Description | Milwaukee® designs and manufactures SAWZALL® blades for the toughest professional applications. Material, blade geometry and heat treating are designed to maximize general purpose cutting performance. |
| Product Type | Blade 10/14TPI 8" |
| Special Features | Double Relief Angle Reduces Tooth Stress For Long Life; Precision Forming Process Creates Sharper Teeth For Fast Cutting; Matrix I Bi-Metal Teeth For Greater Durability; Shank: 1/2 IN Universal; Package Quantity: 5 |
| Manufacturer Information | |
| Brand | Milwaukee® |
| GTIN | 00045242082919 |
| Manufacturers Part Number | 48005193 |
| UPC | 045242082919 |

Taxonomies, Classifications, and Categories

Category Description BITS, BLADES, AND HOLE SAWS



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | |
|-------------------------------------|---------------------|
| Carton | 1 |
| Weight Per each | 0.315 |
| Uses, Certifications, and Standards | |
| Application | For General Purpose |