



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



4887 Conn 15A 125V 2P3W Vinyl STR YI

Eaton Wiring Devices

Catalog Number	4887
Manufacturer	Eaton Wiring Devices
Description	Eaton Arrow Hart Straight Blade Connector , #18-12 Awg, 15A, Commercial, 125V, Back Wire, Yellow, Brass, Vinyl, 5-15R, Two-Pole, Three-Wire, Grounding, Screw, 0.25-0.66", Vinyl, Ed Box
Weight per unit	0.1600 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out

Features

amperage rating	15
core	5-15R
dimensions	2.6000 IN X 1.5000 IN X 1.5000 IN
Material	Vinyl
Resistance	-20 to +60 C
Voltage Rating	5 +/-1 mA

Material, Color, and Finish

Color	Black
Conductor Material	Copper
Insulation Material	PVC
Jacket Material	PVC

Descriptions

Description	CONN 15A 125V 2P3W VINYL STR YL
extra long description	EWD 4887-BOX Conn 15A 125V 2P3W Vin
Features	Our compact yet rugged light commercial and standard residential grade plugs and connectors are available in a broad range of designs, materials and configurations for virtually any replacement application or do-it-yourself extension cord creation.
Long Description	Eaton Arrow Hart straight blade connector , #18-12 AWG, 15A, Commercial, 125V, Back wire, Yellow, Brass, Vinyl, 5-15R, Two-pole, three-wire, grounding, Screw, 0.25-0.66", Vinyl, ED Box
Product Type	Conn 15A 125V 2P3W Vinyl STR YI
Special Features	Spec grade plugs & conns

Manufacturer Information

Brand	Southwire
GTIN	00032664341205
Manufacturers Part Number	4887-BOX
UPC	032664341205



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Residential cord connectors
Type	Straight Blade Connector

Packaging

Carton	10
Package	100
Weight	0.15
Weight Per each	0.16

Uses, Certifications, and Standards

Application	Extension Cord
standard	UL817
Temperature Rating	5-15P