

### ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4250 Business Center Dr. Suite 300 28214-0000, NC Charlotte Phone: 980-249-1969

Fax: 704-900-0948



Width

### **5262WSP TVSS Recp 15A 125V Alarm WH** Pass & Seymour/Legrand

Pass & Seymour/Legra	and
Catalog Number	5262WSP
Manufacturer	Pass & Seymour/Legrand
Description	Surge Protective Extra Heavy-Duty Duplex Receptacle Offers Increased Transient Protection, Reliability and Protection Notification (With Audible Alarm and Led Indicator). Back and Side Wire, 15A, 125V.
Weight per unit	0.3712 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
Features	
amperage rating	15
class	IG
connection	Back and side wire
indoor/outdoor	Indoor
Material	Nylon
media	Yes
Number of Wires	3
Outlet Type	Surge Protected, Straight Blade
Poles	2
Voltage	125.0 V
Voltage Rating	125
Wall Plate Included	NO
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	14 - 10
Material, Color, and Finish	
Color	White
Finish	Matte
Dimensions and Weight	
Height	3.75

1.25



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4250 Business Center Dr. Suite 300 28214-0000, NC Charlotte Phone: 980-249-1969

Fax: 704-900-0948

-				•	
	es	^rı	nt	$\mathbf{I}$	nc
	_				
_	v	<b>v</b> ı .	$\sim$ $\iota$		

Description	TVSS RECP 15A 125V ALARM WH
extra long description	P&S 5262WSP TVSS RECP 15A 125V ALAR
Features	Surge Protection, Single Piece Plated Steel Mounting Strap
Long Description	Surge Protective Extra Heavy-Duty Duplex Receptacle offers increased transient protection, reliability and protection notification (with Audible Alarm and LED Indicator). Back and Side Wire, 15A, 125V.
Product Type	TVSS Recp 15A 125V Alarm WH
Special Features	Solid-state LED monitor has 25-year minimum life expectancy. A high visibility, wide-angle lens indicates protection is in place. LED Indication: steady green = protected, flashing red = not protected, OFF = no power to unit. Audible alarm alert of MOV damage. Alarm able to be turned On/Off. Wrap-around steel strap for structural integrity. Auto-ground is standard, for easier installation. Impact-resistant nylon exterior resists impacts and scrapes. Triple-wipe, copper-alloy contacts for superior, more dep

#### **Manufacturer Information**

Brand	Pass and Seymour
GTIN	00785007193893
Manufacturers Part Number	5262-WSP
UPC	785007193893

#### **Taxonomies, Classifications, and Categories**

Category Description	Commercial receptacies
Type	Spec Grade Surge Protective Receptacle, Audible Alarm with LED
	Indicator
d. C:	

#### **Trade Size**

Amperage	15.0
Amperage	13.0

#### **Packaging**

Carton	1	
Package	50	
Weight Per each	0.3712	



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4250 Business Center Dr. Suite 300 28214-0000, NC Charlotte Phone: 980-249-1969

Fax: 704-900-0948

#### **Uses, Certifications, and Standards**

Application	Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
nema rating	5-15R
standard	CULUS, cUL UL1449, UL498: CSA C22.2 No. 42: ANSI/EEE C62.41 (Formerly IEEE 587), ANSI/IEEE C62.45 Installation Categories "A" (Ring Wave) "B" (Unidirectional Impulse).
Temperature Rating	Operating Temperature: -20°C to +55°C (-4°F to 131°F), Storage Temperature: -40°C to +85°C (-40°F to 185°F)