

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Package

Weight Per each

## **5352GR 1/2" 90D Ebnd Ins LT Flex Conn** *Abb Installation Products, Inc*

| Catalog Number                    | 5352GR   |
|-----------------------------------|--|
| Manufacturer                      | Abb Installation Products, Inc   |
| Description                       | 1/2 Inch External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, 90 Degree Angle, With Revolver Lug, With Tin to Plated Copper Alloy Lug For Awg #14 to #2 Ground Wire, For Use In Wet Locations, 25 Pieces |
| Weight per unit                   | 0.3100 (lbs/each)  |
| Product Category                  | Liquid Tight Fittings  |
| eatures                           |  |
| Material                          | Malleable Iron   |
| Material, Color, and Finish       |  |
| Finish                            | Electro Zinc Plated/Chromate Coating   |
| Dimensions and Weight             |  |
| Size                              | 1/2 INCH   |
| Descriptions                      |  |
| Description                       | 1/2" 90D EBND INS LT FLEX CONN   |
| extra long description            | ABB 5352GR INSUL.90 DEG LIQUIDTITE   |
| Long Description                  | 1/2 Inch External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, 90 Degree Angle, With Revolver Lug, With Tin to plated Copper Alloy Lug for Awg #14 to #2 Ground Wire, for Use In Wet Locations, 25 Pieces |
| Product Type                      | Insul.90 Deg Liquidtite GRD FTG 1/2  |
| Manufacturer Information          |  |
| Brand                             | T&B Ind Fitting  |
| GTIN                              | 00786210900087   |
| Manufacturers Part Number         | 5352GR   |
| UPC                               | 786210900087   |
| axonomies, Classifications, and ( | Categories   |
| Category Description              |  |
| Туре                              | Grounding Connectors-90 degree   |
| Packaging                         |  |
| Carton                            | 25   |
|                                   |  |

50

0.31

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | To positively bond conduit to box or enclosure |
|-------------|--|
| standard    | UL E3060, CSA                                  |