Continued

Arctic	616L	O Clear - medium body PVC solvent cement		
Code	Description	Qty.	Application • Premium polyvinyl chloride (PVC) solvent cement	
55909	½ pt.	24	used for joining PVC pipe and socket-type fittings which meet Clas 12454 as defined in ASTM specification D1784 • Pipe up to 6"	
55919	1 pt.	12	schedule 40; 1-¼" schedule 80 • Remains stable from 0°F to 120°F	
55948	1 qt.	12	Recommended for	
55953	1 gal.	4	Potable water   Pressure pipe	
			Gas • Conduit • Sewers  DWV systems	

#### FEATURES

- · Formulated for use in cold weather LEED compliant
- · NSF approved for potable water
- · 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

## Pete<sup>™</sup>602L

NSI

NSF

Clear - medium	body PVC	solvent	cement
----------------	----------	---------	--------

Also available in gal. can

(PVC) solvent cement used for

40: 1-1/4" for schedule 80 Recommended for • Potable water • Pressure pipe • Gas

Conduit • Sewers

DWV systems

Code	Description	Qty.
55922	¼ pt.	24
55924	½ pt.	24
55926	1 pt.	12
55928	1 qt.	12
55916	1 gal.	4

#### FEATURES

- · Reduces product run-off
- · LEED compliant
- · NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs
- Low-VOC

#### Gene<sup>™</sup>404L $\bigcirc$

### Clear - regular body PVC solvent cement

Code	Description	Qty.
55901	¼ pt.	24
55902	½ pt.	24
55904	1 pt.	12
55906	1 qt.	12
55908	1 gal.	4

# NSE

- 2 year shelf life · Exceeds ASTM D2564

FEATURES

• LEED compliant

Fast setting formula

• NSF approved for potable water

Low-VOC

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints . Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV)

**Recommended for** 

- Potable water
- Pressure pipe Gas
- Conduit 
  Sewers
- DWV systems



LVENT CEN

	1
	T
	N. I
See Contract	

Lew-VOC

www.rectorseal.com