

E26 6" Trim Series

DESCRIPTION

Tapered metal baffle trim with self-flange in the 6" trim family for use in recessed downlighting. Compatible for use in Halo and other housings.


Non-IC

| Catalog # | Туре |
|-------------|------|
| Project | |
| Comments | Date |
| Prepared by | |

SPECIFICATION FEATURES


- · Contoured tapered sides of metal baffle for use with reflector lamps
- Two plastic removable trim rings included narrow 7.25"OD and wide oversized 8.00"OD
- · Coil spring retention

| Housings | | Max Lamp Compatibility | | | | |
|--------------|------------------|---|--|--|--|--|
| H7ICT | H7RICT | | | | | |
| H7ICAT | H7RICAT | - 50W PAR30S, 75W PAR30L, 65W BR3 - 85W BR40 | | | | |
| E7ICAT | E7RICAT | - 0377 51140 | | | | |
| H7UICAT | | 75W PAR30S, 75W PAR30L, 65W BR30, 90W BR40 | | | | |
| H27ICAT | E27ICAT | 50W PAR30S, 75W PAR30L, | | | | |
| H27RICAT | E27RICAT | 65W BR30 | | | | |
| H7T | C7TAT | 75W PAR30S, 75W PAR30L, 65W BR30 | | | | |
| H7TCP | – E7TAT | | | | | |
| H7RT | E7RTAT | - | | | | |
| H27T | E27TAT | - 75W PAR30S, 75W PAR30L, 65W BR30 | | | | |
| H27RT | E27RTAT | 73VV FARSUS, 73VV PARSUL, 03VV BRSU | | | | |
| Compatible w | ith Halogen, Inc | candescent, LED* or CFL* lamps. | | | | |






6100WB White Baffle, Narrow & Wide White Trims (Included)



6100BB Black Baffle, Narrow & Wide White Trims (Included)

6100

6-Inch Tapered Metal Baffles



Dimensions

IC

A: 5-13/16" [148mm] H: 2-7/8" [73mm]

OD: 7-1/4" [184mm] Narrow OD: 8" [203mm] Wide

ORDERING INFORMATION

SAMPLE NUMBER: 6100WB

| Trim | Finish |
|---|---|
| 6100= 6" Tapered Metal Baffle with (2) Trim Rings | WB=White baffle, narrow & wide white trims (included) BB=Black baffle, narrow & wide white trims (included) |

HALO HOUSING COMPATIBILITY

| Trim # | Style | H7ICT | H7ICAT | H7RICT | H7RICAT | E7ICAT | E7RICAT | H7UICAT | H7ICTNB |
|--------|--------|----------|----------|---------|----------|---------|----------|---------|---------|
| 6100 | Baffle | • | • | • | • | • | • | • | _ |
| | | | | | | | | | |
| | | H7ICATNB | E7ICATNB | H27ICAT | H27RICAT | E27ICAT | E27RICAT | | |
| | | _ | _ | • | • | • | • | | |
| | | | | | | | | | |
| | | H7T | H7TCP | H7RT | E7TAT | E7RTAT | H7TNB | E7TATNB | H27T |
| | | • | • | • | • | • | _ | _ | • |
| | | | | | | | | | |
| | | H27RT | E27TAT | E27RTAT | | | | | |
| | | • | • | • | | | | | |

For use in select other's housings, refer to U.L. Classification list at www.cooperlighting.com.

*UL1993 listed LED & CFL equivalent lamps permitted. Consult lamp manufacturer for conditions of use. Cooper Lighting Solutions does not warranty the lamp.



For use in Halo listed housings.



Select trims are classified for use in others housings. See www.cooperlighting.com.

