

ELECTRICAL OUTLET FIRESTOP

Cover Guard[™]

Fire-rated gasket for electrical boxes

Code	Description	Qty.
66272	Single receptacle	50
66270	Double receptacle	50
66276	Single switch	50
66274	Double switch	50
66265	Single decor	50
66266	Double decor	50



• Easy to install · Highly intumescent

• STC rating 54

FEATURES

· Reduces sound transmission

Application • A single component fire-rated gasket for use with electrical boxes to re-establish fire-rating of assemblies with electrical box

penetrations · Fits under the cover plate and does not take up interior box volume



Fire-rated insert for electrical boxes

Code	Description	Qty.
66366	Single box	50
66367	Double box	50
66369	$4^{-11}/_{16}$ " x $4^{-11}/_{16}$ "	50
ASSIFIC	FEATURES	

· Adheres to back of electrical box

- Non-conductive · Highly intumescent
 - STC rating 53

Application • One component fire-rated for use in metal electrical boxes • It is inserted on the inside back wall of an electrical box prior to wiring

US Patent No. 6,207,085; 6,252,167 & 7,348,484



AUK, FIRE FIATED PUTT

US Patent No. 6,207,085 & 6,252,167

Putty Sticks & Pads Fire-rated pad for electrical boxes

Code	Description	Qty.
66345	18 cu./in stick	12
66340	6" x 7" x 1/8" thick	20
66335	7" x 7" x $\frac{1}{8}$ " thick	20
SSIAR CUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUU	 FEATURES Applied by hand No asbestos fillers Pads - STC rating 60 For interior use Adheres to all commo surfaces 	n building

Application • Putty sticks are used to

seal around penetrating items through fire-rated walls, floors and within blank openings Putty pads are used to maintain the hourly rating of fire-rated walls containing electrical outlet boxes and to reduce sound transmission • Hand moldable with no curing time





ELECTRICAL OUTLET FIRESTOP

Cover Guard[™]

Fire-rated gasket for electrical boxes

Code	Description	Qty.
66272	Single receptacle	50
66270	Double receptacle	50
66276	Single switch	50
66274	Double switch	50
66265	Single decor	50
66266	Double decor	50



• Easy to install · Highly intumescent

• STC rating 54

FEATURES

· Reduces sound transmission

Application • A single component fire-rated gasket for use with electrical boxes to re-establish fire-rating of assemblies with electrical box

penetrations · Fits under the cover plate and does not take up interior box volume



Fire-rated insert for electrical boxes

Code	Description	Qty.
66366	Single box	50
66367	Double box	50
66369	$4^{-11}/_{16}$ " x $4^{-11}/_{16}$ "	50
ASSIFIC	FEATURES	

· Adheres to back of electrical box

- Non-conductive · Highly intumescent
 - STC rating 53

Application • One component fire-rated for use in metal electrical boxes • It is inserted on the inside back wall of an electrical box prior to wiring

US Patent No. 6,207,085; 6,252,167 & 7,348,484



AUK, FIRE PATED PUTT

US Patent No. 6,207,085 & 6,252,167

Putty Sticks & Pads Fire-rated pad for electrical boxes

Code	Description	Qty.
66345	18 cu./in stick	12
66340	6" x 7" x 1/8" thick	20
66335	7" x 7" x $\frac{1}{8}$ " thick	20
SSIAR CUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUU	 FEATURES Applied by hand No asbestos fillers Pads - STC rating 60 For interior use Adheres to all commo surfaces 	n building

Application • Putty sticks are used to

seal around penetrating items through fire-rated walls, floors and within blank openings Putty pads are used to maintain the hourly rating of fire-rated walls containing electrical outlet boxes and to reduce sound transmission • Hand moldable with no curing time

