Pass and Seymour
Three Pole Three Phase AC Manual Controller
Part No. 7803MD



Three Pole, Three Phase AC Manual Motor Controller, suitable as Motor Disconnect - 10KA @ 600VAC, 30A max. Class J Fuse.

Features & Benefits

- High Horsepower rating of 20HP
- Constructed of glass-reinforced thermoplastic
- Heavy-duty zinc-plated steel strap, two brass rivets secure strap to housing
- Two oversized silver alloy contacts withstand years of use; improve heat dissipation by distributing arc energy
- Gull-wing shaped brass terminal pressure clamps
- UL508 and cULus Listing of individual device and assembled device within enclosure
- Two-point contact arm design reduces overall unit size
- One-piece contact carrier constructed of glassreinforced thermoplastic ensures long-lasting ""make and break"" performance

Specifications

General Info

Product Line	Pass & Seymour	Color	Black
Finish	Matte	UPC Number	785007267686
Country Of Origin	Mexico	Material	Thermoplastic
Features	Heavy Duty Zinc Plated Steel Strap	Switch Type	Toggle
Number of Switches	1	Application Sector	Commercial, Industrial
Wall Plate Included	No	Standard	CSA Listed, UL Listed
Warranty Type	1-Year Limited Warranty	Type	Manual Controller

Dimensions

Product Width US	1.825 in	Product Depth US	1.753 in
Product Height US	3.67 in		

Listing Agencies / 3rd Party Agencies

cULus Listed	Yes

Technical Information

Load Rating	30 A @ 600 VAC	Operating Cycles	50000
Connection Location	Back and Side	Terminal Accommodation	#14 AWG - #10 AWG
Number of Gangs	1	Throw Type	Single Throw
Amperage	30 A	Number of Poles	3-Way
Requires Neutral Wire	Yes	Indoor/Outdoor	Indoor
Mounting Type	Wall Box	Number of Phases	3
Wire Connection Type	Screw Terminals	Voltage	600.0 V
Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon	Environmental Conditions	UL94 V2

Pass and Seymour
Three Pole Three Phase AC Manual Controller
Part No. 7803MD



Three Pole, Three Phase AC Manual Motor Controller, suitable as Motor Disconnect - 10KA @ 600VAC, 30A max. Class J Fuse.

Features & Benefits

- High Horsepower rating of 20HP
- Constructed of glass-reinforced thermoplastic
- Heavy-duty zinc-plated steel strap, two brass rivets secure strap to housing
- Two oversized silver alloy contacts withstand years of use; improve heat dissipation by distributing arc energy
- Gull-wing shaped brass terminal pressure clamps
- UL508 and cULus Listing of individual device and assembled device within enclosure
- Two-point contact arm design reduces overall unit size
- One-piece contact carrier constructed of glassreinforced thermoplastic ensures long-lasting ""make and break"" performance

Specifications

General Info

Product Line	Pass & Seymour	Color	Black
Finish	Matte	UPC Number	785007267686
Country Of Origin	Mexico	Material	Thermoplastic
Features	Heavy Duty Zinc Plated Steel Strap	Switch Type	Toggle
Number of Switches	1	Application Sector	Commercial, Industrial
Wall Plate Included	No	Standard	CSA Listed, UL Listed
Warranty Type	1-Year Limited Warranty	Type	Manual Controller

Dimensions

Product Width US	1.825 in	Product Depth US	1.753 in
Product Height US	3.67 in		

Listing Agencies / 3rd Party Agencies

cULus Listed	Yes

Technical Information

Load Rating	30 A @ 600 VAC	Operating Cycles	50000
Connection Location	Back and Side	Terminal Accommodation	#14 AWG - #10 AWG
Number of Gangs	1	Throw Type	Single Throw
Amperage	30 A	Number of Poles	3-Way
Requires Neutral Wire	Yes	Indoor/Outdoor	Indoor
Mounting Type	Wall Box	Number of Phases	3
Wire Connection Type	Screw Terminals	Voltage	600.0 V
Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon	Environmental Conditions	UL94 V2