



# Fluorescent Lampholders

## Low Profile Long Twin Tube Lampholders

### 2G11 Lampholders



**80-1600**  
Horizontal Snap-In Mounting  
Multiple Bottom Push-In Wiring Ports  
Metal-Spring Lamp Retainer Clip  
1 5/8" H x 1 7/8" W x 7/8" Dia.  
660W-600V



**80-1601**  
Shunted Horizontal Snap-In Mounting  
for Electronic Ballasts  
Bottom Push-In Wiring  
1 5/8" H x 1 7/8" W x 7/8" Dia.  
660W-600V



**80-1602**  
Shunted Vertical Snap-In Mounting for  
Electronic Ballasts, Side Push-In Wiring  
Wireways Allow Routing on Top  
or Bottom of Mounting Panel  
2" H x 1 1/4" W x 7/8" Dia.  
660W-600V

### 2GX7 Lampholder



**80-2350**  
Horizontal Screw Mount  
w/Two Holes  
1 1/8" H x 1 5/8" W x 1 3/4" Dia.

### 2G11 Lamp Support Clips



**80-1603**  
Clear Vertical Clip  
UV Stable Polycarbonate  
Panel Thickness  
.023 - .039 (0.58-0.99) Max.  
1 5/8" H x 7/8" W x 3/8" Dia.



**80-1604**  
Clear Horizontal Clip  
UV Stable Polycarbonate  
Panel Thickness  
.023 - .039 (0.58-0.99) Max.  
1 1/4" H x 1 5/8" W x 3/8" Dia.

### 4-Pin Long Twin Tube Lampholder & Clips



**80-1605**  
4-Pin Long Twin Tube Lampholder  
Molded White Thermosetting Urea  
Copper Alloy, Double-Edge Contacts  
Push-In Wiring  
Accepts 18 AWG Leads - Solid, Solder  
Dipped or Twisted, Tinned & Fused  
1 7/8" H x 2 1/8" W x 7/8" Dia.  
660W-600V



**80-1606**  
Clear Plastic Horizontal Clip  
Panel Thickness  
.023 - .039 (0.58-0.99) Max.  
1 1/4" H x 1 5/8" W x 1/2" Dia.

### T-8 Clip



**80-2119**  
Stainless Steel Clip  
for Lamp Support

### Circline Clip



**90-935**  
Circline Fluorescent  
Clip



# Fluorescent Lampholders

## Low Profile Long Twin Tube Lampholders

### 2G11 Lampholders



**80-1600**  
Horizontal Snap-In Mounting  
Multiple Bottom Push-In Wiring Ports  
Metal-Spring Lamp Retainer Clip  
1 5/8" H x 1 7/8" W x 7/8" Dia.  
660W-600V



**80-1601**  
Shunted Horizontal Snap-In Mounting  
for Electronic Ballasts  
Bottom Push-In Wiring  
1 5/8" H x 1 7/8" W x 7/8" Dia.  
660W-600V



**80-1602**  
Shunted Vertical Snap-In Mounting for  
Electronic Ballasts, Side Push-In Wiring  
Wireways Allow Routing on Top  
or Bottom of Mounting Panel  
2" H x 1 1/4" W x 7/8" Dia.  
660W-600V

### 2GX7 Lampholder



**80-2350**  
Horizontal Screw Mount  
w/Two Holes  
1 1/8" H x 1 5/8" W x 1 3/4" Dia.

### 2G11 Lamp Support Clips



**80-1603**  
Clear Vertical Clip  
UV Stable Polycarbonate  
Panel Thickness  
.023 - .039 (0.58-0.99) Max.  
1 5/8" H x 7/8" W x 3/8" Dia.



**80-1604**  
Clear Horizontal Clip  
UV Stable Polycarbonate  
Panel Thickness  
.023 - .039 (0.58-0.99) Max.  
1 1/4" H x 1 5/8" W x 3/8" Dia.

### 4-Pin Long Twin Tube Lampholder & Clips



**80-1605**  
4-Pin Long Twin Tube Lampholder  
Molded White Thermosetting Urea  
Copper Alloy, Double-Edge Contacts  
Push-In Wiring  
Accepts 18 AWG Leads - Solid, Solder  
Dipped or Twisted, Tinned & Fused  
1 7/8" H x 2 1/8" W x 7/8" Dia.  
660W-600V



**80-1606**  
Clear Plastic Horizontal Clip  
Panel Thickness  
.023 - .039 (0.58-0.99) Max.  
1 1/4" H x 1 5/8" W x 1/2" Dia.

### T-8 Clip



**80-2119**  
Stainless Steel Clip  
for Lamp Support

### Circline Clip



**90-935**  
Circline Fluorescent  
Clip